

HP E14 G4 Portable - LED monitor - Full HD (1080p) - 14" - HDR



In Stock(115)

SKU	1B065AA#ABB
Product Description:	HP E14 G4 Portable - LED monitor - Full HD (1080p) - 14" - HDR
Device Type:	LED-backlit LCD monitor - 14"
Energy Class:	Class B
Panel Type:	IPS
Aspect Ratio:	16:9
Native Resolution:	Full HD (1080p) 1920 x 1080 at 60 Hz
Pixel Pitch:	0.1611 mm

General

Display Type:	LED-backlit LCD monitor / TFT active matrix
Energy Class:	Class B
Diagonal Size:	14"
Panel Type:	IPS
Aspect Ratio:	16:9
Native Resolution:	Full HD (1080p) 1920 x 1080 at 60 Hz
Pixel Pitch:	0.1611 mm
Pixel Per Inch:	157
Brightness:	400 cd/m ²
Contrast Ratio:	800:1 / 5000000:1 (dynamic)
Colour Gamut:	72% NTSC
Response Time:	5 ms (grey-to-grey with overdrive)
Vertical Refresh Rate:	59 - 60 Hz
Horizontal Refresh Rate:	30 - 80 kHz

Environmental Parameters

Min Operating Temperature:	5 °C
Max Operating Temperature:	35 °C
Humidity Range Operating:	20 - 80% (non-condensing)

Manufacturer Warranty

Service & Support:	Limited warranty - parts and labour - 3 years
--------------------	---

Sustainability Information

ENERGY STAR Certified:	Yes
ENERGY STAR Version:	8.0

Dimensions & Weight (Shipping)

Shipping Width:	40.5 cm
Shipping Depth:	6.1 cm
Shipping Height:	28.4 cm
Shipping Weight:	1.54 kg

Dimensions & Weight

Dimensions & Weight Details:	With stand - width: 32.14 cm - depth: 1.52 cm - height: 21 cm - weight: 640 g With stand - width: 32.14 cm
------------------------------	--

General

Horizontal Viewing Angle: 178

Vertical Viewing Angle: 178

Screen Coating: Anti-glare 3H hardness, Haze 24%

Backlight Technology: Edge-lit LED

OSD Languages: Chinese (traditional), Chinese (simplified), English, German, French, Italian, Portuguese, Spanish, Dutch, Japanese

Features: On-screen Digital Controls, Low Blue Light Mode, Flicker Free technology, Mercury free, arsenic-free glass, 3-sided micro-edge, 8-bit Colour Depth, 72% NTSC colour gamut

Colour: Silver stand

Dimensions (WxDxH): 32.14 cm x 1.52 cm x 21 cm - with stand

Weight: 640 g

Connectivity

Interfaces: 2 x USB-C/DisplayPort 1.2 Alt Mode

Power

Power Consumption SDR (On mode): 5.4 kWh/1000h

Power Consumption (Typical): 6 Watt

Power Consumption Stand by: 0.3 Watt

Miscellaneous

Included Accessories: Sleeve

Cables Included: 1 x USB-C cable

Backlight Life: 15,000 hours

Compliant Standards: UL, TUV, TUV GS, VCCI, BSMI, NOM, WHQL, CB, CCC, FCC, ISO 9241-307, KCC, WEEE, Green Mark, ICES, cTUVus, KC, EAC, ISC, BIS, low halogen, UAE, Vietnam MEPS

Localisation: English / Europe

Mechanical

Display Position Adjustments: Tilt

Tilt Angle: 0/+78

