

HP E24i G4 - E-Series - LED monitor - 24"



In Stock(292)

SKU	9VJ40A3#ABB
Product Description:	HP E24i G4 - E-Series - LED monitor - 24"
Device Type:	LED-backlit LCD monitor - 24"
Energy Class:	Class D
Energy Consumption per Year:	24 kWh
Power Consumption (On mode):	15.3 W
Features:	USB 3.2 Gen 1 hub
Panel Type:	IPS

General

Display Type: LED-backlit LCD monitor / TFT active matrix

Energy Class: Class D

Energy Consumption per Year: 24 kWh

Diagonal Size: 24"

Built-in Devices: USB 3.2 Gen 1 hub

Panel Type: IPS

Aspect Ratio: 16:10

Native Resolution: WUXGA 1920 x 1200 at 60 Hz

Pixel Pitch: 0.2745 mm

Pixel Per Inch: 94

Brightness: 250 cd/m²

Contrast Ratio: 1000:1 / 5000000:1 (dynamic)

Colour Support: 16.7 million colours (8-bit)

Colour Gamut: 72% (CIE 1931), 83% (CIE 1976)

Response Time: 5 ms (grey-to-grey with overdrive)

Environmental Parameters

Min Operating Temperature: 5 °C

Max Operating Temperature: 35 °C

Humidity Range Operating: 20 - 80% (non-condensing)

Manufacturer Warranty

Service & Support: Limited warranty - parts and labour - 3 years

Sustainability Information

TCO Certified: TCO Certified Displays 8, TCO Certified Edge Displays

ENERGY STAR Certified: Yes

Dimensions & Weight (Shipping)

Shipping Width: 60.5 cm

Shipping Depth: 42 cm

Shipping Height: 22.4 cm

Shipping Weight: 9.12 kg

Dimensions & Weight

General

Vertical Refresh Rate:	50 - 60 Hz
Horizontal Refresh Rate:	30 - 80 kHz
Horizontal Viewing Angle:	178
Vertical Viewing Angle:	178
Screen Coating:	Haze 25%, anti-glare 3H hardness
Backlight Technology:	LED backlight
Colour Temperature:	6500K
OSD Languages:	Chinese (traditional), Chinese (simplified), English, German, French, Italian, Portuguese, Spanish, Dutch, Japanese
Features:	HDCP, Low Blue Light Mode, 3-sided micro-edge, 8-bit Colour Depth, HP Eye Ease
Colour:	Black
Dimensions (WxDxH):	53.2 cm x 20.69 cm x 50.96 cm - with stand
Weight:	6.06 kg

Connectivity

Interfaces:	DisplayPort 1.2 HDMI VGA 3 x USB 3.2 Gen 1 downstream (fast charging) USB 3.2 Gen 1 upstream (Type B)
-------------	---

Mechanical

Display Position Adjustments:	Height, pivot (rotation), swivel, tilt
Tilt Angle:	-5/+23
Swivel Angle:	90
Rotation Angle:	180
Height Adjustment:	150 mm

Dimensions & Weight

Dimensions & Weight Details:	With stand - width: 53.2 cm - depth: 20.69 cm - height: 50.96 cm - weight: 6.06 kg
	Without stand - width: 53.2 cm - depth: 4.7 cm - height: 35.27 cm - weight: 3.6 kg

Software / System Requirements

Included Software:	HP Display Assistant
--------------------	----------------------

Power

Input Voltage:	AC 120/230 V (50/60 Hz)
Power Consumption (On mode):	15.3 W
Power Consumption SDR (On mode):	15.3 kWh/1000h
Power Consumption (Typical):	36 Watt
Power Consumption Stand by:	0.5 Watt

Miscellaneous

Features:	Security lock slot (cable lock sold separately), detachable stand, arsenic free, mercury free
Backlight Life:	30,000 hours
Compliant Standards:	Plug and Play, TUV GS, VCCI, BSMI, NOM, TUV S, CB, CCC, PSB, FCC, ISO 9241-307, KCC, WEEE, cTUVus, E-Standby, CEC, KC, CECP, CEL, EAC, CEL Grade 1, ISC, BIS, low halogen, DisplayPort 1.2, HP GSE, Australian-New Zealand MEPS, Vietnam MEPS
Localisation:	English / Europe
Security Slot Type:	Kensington security slot

Mechanical

VESA Mounting
Interface:

100 x 100 mm

