

HP E24mv G4 Conferencing Monitor - E-Series - LED monitor - Full HD (1080p) - 23.8"



Not in stock

SKU	169LOAA#ABB
Product Description:	HP E24mv G4 Conferencing Monitor - E-Series - LED monitor - Full HD (1080p) - 23.8"
Device Type:	LED-backlit LCD monitor - 23.8"
Energy Class:	Class E
Features:	IR camera, USB 3.2 Gen 1 hub
Panel Type:	IPS
Aspect Ratio:	16:9
Native Resolution:	Full HD (1080p) 1920 x 1080 at 60 Hz

General

Display Type:	LED-backlit LCD monitor / TFT active matrix
Energy Class:	Class E
Diagonal Size:	23.8"
Built-in Devices:	IR camera, USB 3.2 Gen 1 hub
Panel Type:	IPS
Aspect Ratio:	16:9
Native Resolution:	Full HD (1080p) 1920 x 1080 at 60 Hz
Pixel Pitch:	0.2745 mm
Pixel Per Inch:	93
Brightness:	250 cd/m ²
Contrast Ratio:	1000:1 / 5000000:1 (dynamic)
Colour Gamut:	72% NTSC
Response Time:	5 ms (grey-to-grey with overdrive)
Vertical Refresh Rate:	50 - 60 Hz

Environmental Parameters

Min Operating Temperature:	5 °C
Max Operating Temperature:	35 °C
Humidity Range Operating:	20 - 80% (non-condensing)

Manufacturer Warranty

Service & Support:	Limited warranty - 3 years
--------------------	----------------------------

Sustainability Information

TCO Certified:	TCO Certified Displays 9
ENERGY STAR Certified:	Yes

Dimensions & Weight (Shipping)

Shipping Width:	59.6 cm
Shipping Depth:	22.5 cm
Shipping Height:	41.1 cm
Shipping Weight:	10.4 kg

Dimensions & Weight

General

Horizontal Refresh Rate: 30 - 80 kHz

Horizontal Viewing Angle: 178

Vertical Viewing Angle: 178

Screen Coating: Anti-glare, 3H Hard Coating, Haze 25%

Backlight Technology: LED backlight

Colour Temperature: 6500K

OSD Languages: Chinese (traditional), Chinese (simplified), English, German, French, Italian, Portuguese, Spanish, Dutch, Japanese

Features: HDCP, On-screen Digital Controls, Low Blue Light Mode, Flicker Free technology, 3-sided micro-edge, edge-lit LED backlight, 8-bit(6-bit + FRC) Colour Depth, HP Eye Ease, 72% NTSC colour gamut

Colour: Silver, black head

Dimensions (WxDxH): 53.94 cm x 21.6 cm x 53.07 cm - with stand

Weight: 6.5 kg

Audio Input

Type: Microphone

Audio

Type: Speakers - stereo

Output Power / Channel: 2 Watt

Connectivity

Interfaces: DisplayPort 1.2 | HDMI | VGA | 4 x USB 3.2 Gen 1 upstream | USB (Type B) | Audio line-out (mini-jack)

Dimensions & Weight

Dimensions & Weight Details: With stand - width: 53.94 cm - depth: 21.6 cm - height: 53.07 cm - weight: 6.5 kg | Without stand - width: 53.94 cm - depth: 4.7 cm - height: 35.56 cm - weight: 3.9 kg

Software / System Requirements

Included Software: HP Display Center

Power

Input Voltage: AC 120/230 V (50/60 Hz)

Power Consumption SDR (On mode): 16 kWh/1000h

Power Consumption (Typical): 28 Watt

Power Consumption (Max): 50 Watt

Power Consumption Stand by: 0.5 Watt

Miscellaneous

Features: Security lock slot (cable lock sold separately), volume control, detachable stand, VESA interface support, arsenic free, mercury free, microphone mute control

Cables Included: 1 x DisplayPort 1.2 cable - 1.8 m | 1 x HDMI cable - 1.8 m | 1 x USB-A to USB-B cable - 1.8 m

Backlight Life: 30,000 hours

Compliant Standards: TUV GS, VCCI, BSMI, GS, NOM, WHQL, CB, CCC, PSB, FCC, ISO 9241-307, KCC, WEEE, MEPS, KC, CECP, CEL, SEPA, BIS, low halogen, DisplayPort 1.2, Ukraine, UAE, Australian-New Zealand MEPS, Vietnam MEPS

Localisation: English / Europe

Security Slot Type: Kensington security slot

Mechanical

Display Position Adjustments: Height, pivot (rotation), swivel, tilt



Mechanical

Tilt Angle:	-5/+23
Swivel Angle:	90
Rotation Angle:	180
Height Adjustment:	150 mm
VESA Mounting Interface:	100 x 100 mm