

HP E34m G4 Conferencing Monitor - E-Series - LED monitor - curved - 34"



In Stock(100)

SKU	40Z26AA#ABB
Product Description:	HP E34m G4 Conferencing Monitor - E-Series - LED monitor - curved - 34"
Device Type:	LED-backlit LCD monitor - 34"
Energy Class:	Class G
Power Consumption (On mode):	39 W
Curved Screen:	Yes
Features:	IR camera, USB 3.2 Gen 1 hub, USB PD 65 Watt
Panel Type:	VA

General

Display Type: LED-backlit LCD monitor / TFT active matrix

Energy Class: Class G

Diagonal Size: 34"

Curved Screen: Yes (1500R)

Built-in Devices: IR camera, USB 3.2 Gen 1 hub

USB Power Delivery: 65 Watt

Panel Type: VA

Aspect Ratio: 21:9

Native Resolution: WQHD 3440 x 1440 at 75 Hz

Pixel Pitch: 0.23175 mm

Pixel Per Inch: 110

Brightness: 400 cd/m²

Contrast Ratio: 3000:1 / 10000000:1 (dynamic)

Colour Support: 16.7 million colours

Colour Gamut: 99% sRGB

Environmental Parameters

Min Operating Temperature: 5 °C

Max Operating Temperature: 35 °C

Humidity Range Operating: 20 - 80% (non-condensing)

Sustainability Information

TCO Certified: TCO Certified Displays 9

ENERGY STAR Certified: Yes

Dimensions & Weight (Shipping)

Shipping Width: 90.5 cm

Shipping Depth: 28.1 cm

Shipping Height: 48.1 cm

Shipping Weight: 17.69 kg

Dimensions & Weight

Dimensions & Weight Details: Without stand - width: 80.83 cm - depth: 10.91 cm - height: 38.81 cm ; With stand - width: 80.83 cm - depth: 23.3 cm - height: 54.32 cm - weight: 11.98 kg

Software / System Requirements

General

Response Time:	5 ms (grey-to-grey with overdrive)
Vertical Refresh Rate:	48 - 75 Hz
Horizontal Refresh Rate:	30 - 150 kHz
Horizontal Viewing Angle:	178
Vertical Viewing Angle:	178
Screen Coating:	Anti-glare, 3H Hard Coating, Haze 25%
Backlight Technology:	LED backlight
Colour Temperature:	6500K
OSD Languages:	Chinese (traditional), Chinese (simplified), English, German, French, Italian, Portuguese, Spanish, Dutch, Japanese
Features:	HDCP, Flicker Free technology, 3-sided micro-edge, Low Blue Light technology, 8-bit Colour Depth, edge-lit LED backlight, HP Eye Ease, pop-up webcam, Zoom Certified
Colour:	Silver (stand), black head
Dimensions (WxDxH):	80.83 cm x 23.3 cm x 54.32 cm - with stand
Weight:	11.98 kg

Audio Input

Type:	Microphone
Microphone Features:	Echo cancellation

Audio

Type:	Speakers - stereo
Output Power / Channel:	5 Watt

Connectivity

Software / System Requirements

Included Software:	HP Display Assistant
--------------------	----------------------

Power

Input Voltage:	AC 120/230 V (50/60 Hz)
Power Consumption (On mode):	39 W
Power Consumption SDR (On mode):	32 kWh/1000h
Power Consumption (Typical):	65 Watt
Power Consumption (Max):	185 Watt
Power Consumption Stand by:	0.5 Watt

Miscellaneous

Features:	Security lock slot (cable lock sold separately), detachable stand, VESA interface support
-----------	---

Included Accessories:	Mount adapter
-----------------------	---------------

Cables Included:	1 x USB-C cable
------------------	-----------------

Mounting Kit:	Included
---------------	----------

Backlight Life:	30,000 hours
-----------------	--------------

Compliant Standards:	TUV GS, VCCI, BSMI, NOM, TUV S, CB, CCC, PSB, FCC, ISO 9241-307, KCC, WEEE, cTUVus, E-Standby, KC, CECP, EAC, CEL Grade 1, ISC, RCM, SEPA, BIS, low halogen, DisplayPort 1.2, Energy-using Products (EuP) Lot 5, ICE, SmartWay, NRCS, Mexico Energy label, Ukraine, UAE, TGM, Belarus Energy
----------------------	--

Localisation:	English / Europe
---------------	------------------

Security Slot Type:	Kensington security slot
---------------------	--------------------------

Mechanical

Display Position Adjustments:	Height, swivel, tilt
-------------------------------	----------------------

Tilt Angle:	-5/+20
-------------	--------

Swivel Angle:	60
---------------	----

Connectivity

Interfaces: DisplayPort 1.2 (HDCP) ; HDMI (HDCP) ;
USB-C 3.2 Gen 1 (power up to 65W) ; 4 x
USB 3.2 Gen 1 ; LAN ; Audio line-in/out
(mini-jack)

Mechanical

Height Adjustment:	150 mm
VESA Mounting Interface:	100 x 100 mm

