

HP EliteDisplay E273 - LED monitor - Full HD (1080p) - 27"



Not in stock

SKU	1FH50AA#ABB
Product Description:	HP EliteDisplay E273 - LED monitor - Full HD (1080p) - 27"
Device Type:	LED-backlit LCD monitor - 27"
Energy Class:	Class E
Energy Consumption per Year:	24 kWh
Power Consumption (On mode):	20.2 W
Features:	USB 3.0 hub
Panel Type:	IPS

General

Display Type:	LED-backlit LCD monitor / TFT active matrix
Energy Class:	Class E
Energy Consumption per Year:	24 kWh
Diagonal Size:	27"
Built-in Devices:	USB 3.0 hub
Panel Type:	IPS
Aspect Ratio:	16:9
Native Resolution:	Full HD (1080p) 1920 x 1080 at 60 Hz
Pixel Pitch:	0.3114 mm
Pixel Per Inch:	81.59
Brightness:	250 cd/m ²
Contrast Ratio:	1000:1 / 5000000:1 (dynamic)
Colour Support:	16.7 million colours
Colour Gamut:	72% NTSC, 94% sRGB
Response Time:	5 ms (On/Off)

Environmental Parameters

Min Operating Temperature:	5 °C
Max Operating Temperature:	35 °C
Humidity Range Operating:	20 - 80% (non-condensing)

Manufacturer Warranty

Service & Support:	Limited warranty - 3 years
--------------------	----------------------------

Sustainability Information

ENERGY STAR Certified:	Yes
------------------------	-----

Dimensions & Weight

Dimensions & Weight Details:	With stand - width: 61.09 cm - depth: 21.39 cm - height: 52.26 cm - weight: 7.1 kg Without stand - width: 61.09 cm - depth: 5.02 cm - height: 36.4 cm - weight: 4.48 kg
------------------------------	---

Software / System Requirements

Included Software:	HP Display Assistant
--------------------	----------------------

Power

Input Voltage:	AC 120/230 V (50/60 Hz)
----------------	-------------------------

General

Vertical Refresh Rate:	50 - 60 Hz
Horizontal Refresh Rate:	30 - 80 kHz
Horizontal Viewing Angle:	178
Vertical Viewing Angle:	178
Screen Coating:	Anti-glare, 3H Hard Coating
Backlight Technology:	WLED
Colour Temperature:	6500K
OSD Languages:	Chinese (traditional), Chinese (simplified), English, German, French, Italian, Portuguese, Spanish, Dutch, Japanese
Features:	HDCP, Frame Rate Control (FRC), Low Blue Light Mode, Flicker Free technology, Mercury free, arsenic-free glass, Micro Edge, 72% NTSC colour gamut
Colour:	Black (rear cover), silver (front bezel, frame and stand)
Dimensions (WxDxH):	61.09 cm x 21.39 cm x 52.26 cm - with stand
Weight:	7.1 kg

Connectivity

Interfaces:	HDMI (HDCP) ; DisplayPort (HDCP) ; VGA ; USB 3.0 upstream (Type B) ; 2 x USB 3.0 downstream (Type A)
-------------	--

Power

Power Consumption (On mode):	20.2 W
Power Consumption SDR (On mode):	20.2 kWh/1000h
Power Consumption (Typical):	45 Watt
Power Consumption Stand by:	0.3 Watt
On / Off Switch:	Yes

Miscellaneous

Features:	Security lock slot (cable lock sold separately), integrated cable management, detachable stand, direct mountable, VESA interface support
Cables Included:	1 x VGA cable - 1.8 m ; 1 x DisplayPort cable - 1.8 m ; 1 x USB 3.0 to USB 3.0 type B cable - 1.8 m
Backlight Life:	30,000 hours
Compliant Standards:	Plug and Play, CSA, UL, VCCI, BSMI, NOM, TUV S, WHQL, CB, CCC, PSB, FCC, ISO 9241-307, KCC, WEEE, MEPS, KC, CECP, CEL, EAC, ISC, low halogen, ICE, SmartWay
Localisation:	English / Europe
Security Slot Type:	Kensington security slot

Mechanical

Display Position Adjustments:	Height, pivot (rotation), swivel, tilt
Tilt Angle:	-5/+22
Swivel Angle:	90
Rotation Angle:	180
Height Adjustment:	150 mm
VESA Mounting Interface:	100 x 100 mm