

HP EliteDisplay E273q - LED monitor - 27"



Not in stock

SKU	1FH52AA#ABB
Product Description:	HP EliteDisplay E273q - LED monitor - 27"
Device Type:	LED-backlit LCD monitor - 27"
Energy Class:	Class G
Power Consumption (On mode):	30 W
Features:	USB 3.0 hub
Panel Type:	IPS
Aspect Ratio:	16:9

General

Display Type:	LED-backlit LCD monitor / TFT active matrix
Energy Class:	Class G
Diagonal Size:	27"
Built-in Devices:	USB 3.0 hub
Panel Type:	IPS
Aspect Ratio:	16:9
Native Resolution:	QHD 2560 x 1440 at 60 Hz
Pixel Pitch:	0.2331 mm
Pixel Per Inch:	108.8
Brightness:	350 cd/m ²
Contrast Ratio:	1000:1 / 5000000:1 (dynamic)
Colour Support:	16.7 million colours
Colour Gamut:	99.6% sRGB
Response Time:	5 ms (On/Off)
Vertical Refresh Rate:	50 - 60 Hz
Horizontal Refresh Rate:	30 - 90 kHz

Environmental Parameters

Min Operating Temperature:	5 °C
Max Operating Temperature:	35 °C
Humidity Range Operating:	20 - 80% (non-condensing)

Manufacturer Warranty

Service & Support:	Limited warranty - 3 years
--------------------	----------------------------

Sustainability Information

ENERGY STAR Certified:	Yes
------------------------	-----

Dimensions & Weight

Dimensions & Weight Details:	With stand - width: 61.26 cm - depth: 21.4 cm - height: 52.29 cm - weight: 7.4 kg Without stand - width: 61.26 cm - depth: 4.93 cm - height: 36.4 cm - weight: 4.6 kg
------------------------------	--

Software / System Requirements

Included Software:	HP Display Assistant
--------------------	----------------------

Power

Input Voltage:	AC 120/230 V (50/60 Hz)
----------------	-------------------------

General

Horizontal Viewing Angle: 178

Vertical Viewing Angle: 178

Screen Coating: Anti-glare, 3H Hard Coating

Backlight Technology: WLED

Colour Temperature: 6500K

OSD Languages: Chinese (traditional), Chinese (simplified), English, German, French, Italian, Portuguese, Spanish, Dutch, Japanese

Features: HDCP, Frame Rate Control (FRC), Low Blue Light Mode, Flicker Free technology, Mercury free, arsenic-free glass, Micro Edge

Colour: Black (rear cover), silver (front bezel, frame and stand)

Dimensions (WxDxH): 61.26 cm x 21.4 cm x 52.29 cm - with stand

Weight: 7.4 kg

Connectivity

Interfaces: HDMI (HDCP) ; DisplayPort (HDCP) ; VGA ; USB-C upstream (HDCP) ; 2 x USB 3.0 downstream (Type A)

Power

Power Consumption (On mode): 30 W

Power Consumption SDR (On mode): 30 kWh/1000h

Power Consumption (Typical): 75 Watt

Power Consumption Stand by: 0.5 Watt

On / Off Switch: Yes

Miscellaneous

Features: Security lock slot (cable lock sold separately), integrated cable management, detachable stand, direct mountable, VESA interface support

Cables Included: 1 x HDMI cable - 1.8 m ; 1 x DisplayPort cable - 1.8 m ; 1 x USB 3.1 Type A to Type C cable - 1.8 m

Backlight Life: 30,000 hours

Compliant Standards: Plug and Play, TUV GS, VCCI, BSMI, TUV S, WHQL, CB, CCC, PSB, FCC, ISO 9241-307, WEEE, PSE Mark, cTUVus, MEPS, CECP, CEL, EAC, ISC, RCM, MSIP, CoC, low halogen, ICE, SmartWay

Localisation: English / Europe

Security Slot Type: Kensington security slot

Mechanical

Display Position Adjustments: Height, pivot (rotation), swivel, tilt

Tilt Angle: -5/+22

Swivel Angle: 90

Rotation Angle: 180

Height Adjustment: 150 mm

VESA Mounting Interface: 100 x 100 mm

