

HP Engage One 10t - customer display - 10.1"



14-05-2024

SKU	1XD81AA#AC3
Product Description:	HP Engage One 10t - customer display - 10.1"
Device Type:	Customer display - 10.1" - touchscreen
Energy Class:	Class E
Panel Type:	IPS
Aspect Ratio:	16:10
Native Resolution:	1280 x 800 at 60 Hz
Pixel Pitch:	0.1695 mm

General

Display Type:	Customer display / TFT active matrix
Energy Class:	Class E
Diagonal Size:	10.1"
Panel Type:	IPS
Aspect Ratio:	16:10
Native Resolution:	1280 x 800 at 60 Hz
Pixel Pitch:	0.1695 mm
Pixel Per Inch:	149
Brightness:	500 cd/m ²
Contrast Ratio:	800:1
Colour Support:	16.9 million colours
Colour Gamut:	45%
Response Time:	25 ms
Vertical Refresh Rate:	50 - 60 Hz
Horizontal Refresh Rate:	30 - 54 kHz
Horizontal Viewing Angle:	170

Compatibility Information

Designed For:	HP Engage One
---------------	---------------

Environmental Parameters

Min Operating Temperature:	5 °C
Max Operating Temperature:	35 °C
Humidity Range Operating:	20 - 80% (non-condensing)

Sustainability Information

ENERGY STAR Certified:	Yes
------------------------	-----

Dimensions & Weight (Shipping)

Shipping Width:	30.6 cm
Shipping Depth:	11 cm
Shipping Height:	23.2 cm
Shipping Weight:	1.93 kg

Dimensions & Weight

Dimensions & Weight Details:	With stand - width: 24.62 cm - height: 17.02 cm - weight: 1.49 kg
------------------------------	---

Power

Power Consumption SDR (On mode):	9 kWh/1000h
----------------------------------	-------------

Miscellaneous

General

Vertical Viewing Angle: 170

Backlight Technology: LED backlight

Colour Temperature: 6500K

OSD Languages: Chinese (traditional), Chinese (simplified), English, German, French, Italian, Portuguese, Spanish, Japanese

Features: Anti-glare, edge-to-edge glass, Mercury free, arsenic free

Colour: Black bezel and hinge

Dimensions (WxDxH): 24.62 cm x 1.5 cm x 17.02 cm - without stand

Input

Type: Touchscreen

Miscellaneous

Backlight Life: 50,000 hours

Compliant Standards: Plug and Play, VCCI, BSMI, WHQL, CB, CCC, FCC, ISO 9241-307, WEEE, ICES, cTUVus, TUV Bauart, EAC, RCM, MSIP, CoC, low halogen, Morocco

Mechanical

Display Position Adjustments: Tilt

Tilt Angle: 105

Connectivity

Interfaces: USB-C upstream

