

HP JetDirect 2800w - print server



In Stock(8)

SKU	J8029A
Product Description:	HP JetDirect 2800w - print server
Device Type:	Print server
Form Factor:	External
Dimensions (WxDxH):	9.6 cm x 7.3 cm x 2.1 cm
Weight:	80 g
Data Link Protocol:	802.11b/g, NFC
Max Transfer Distance:	15 m

General

Device Type:	Print server
Form Factor:	External

Networking

Connectivity Technology:	Wireless
Data Link Protocol:	IEEE 802.11b, IEEE 802.11g, NFC
Max Transfer Distance:	15 m
Network / Transport Protocol:	ICMP/IP, LPR/LPD, FTP, DHCP, Bonjour, SLP
Remote Management Protocol:	SNMP 1, Telnet, SNMP 3, IPP, SNMP 2c, HTTP, HTTPS
Features:	IPv6 support, firmware upgradable, web server, IPv4 support
Compliant Standards:	IEEE 802.11b, IEEE 802.11g

Miscellaneous

Cables Included:	2 x mini-USB cable
Encryption Algorithm:	AES, SSL, TLS, WPA2

Compatibility Information

Designed For:	HP Color LaserJet Enterprise M651dn, M651n, M651xh, M855dn, M855x+, M855x+ NFC/Wireless direct, M855xh, MFP M575dn, MFP M575f, MFP M680dn, MFP M680f, MFP M775dn, MFP M775f, MFP M775z, MFP M775z+ ; HP Color LaserJet Managed M651dnm, M651xhm ; HP Color LaserJet Managed Flow MFP M680zm, MFP M880zm, MFP M880zm+ ; HP LaserJet Enterprise 500 M551dn, 500 M551n, 500 M551xh, 700 Printer M712dn, 700 Printer M712n, 700 Printer M712xh, M806dn, M806x+, M806x+ NFC/Wireless direct, MFP M525dn, MFP M525f, MFP M630dn, MFP M630f, MFP M630h, MFP M725dn, MFP M725f, MFP M725z, MFP M725z+ ; HP LaserJet Enterprise Flow MFP M525c, MFP M575c, MFP M630h, MFP M630z, MFP M680z, MFP M830z, MFP M830z NFC/Wireless direct, MFP M880z, MFP M880z+, MFP M880z+ NFC/Wireless direct ; HP LaserJet Managed MFP M525fm, MFP M575dnm, MFP M630hm, MFP M680dnm, MFP M725dnm, MFP M725zm ; HP LaserJet Managed Flow MFP M525cm, MFP M575cm, MFP M630hm, MFP M630zm, MFP M830zm ; HP Officejet Enterprise Color MFP X585dn, MFP X585f, X555dn, X555xh ; HP Officejet Enterprise Color Flow MFP X585z ; HP Officejet Managed Color MFP X585dnm ; HP Officejet Managed Color Flow MFP X585zm ; HP PageWide Pro 452dw, 477dn, 477dw, 552dw, 577dw
---------------	---

Miscellaneous

	UL, FCC Part 15.247, RSS-210, FCC CFR47 Part 15 B, Directive 2004/108/EC, BFR,
Compliant	Directive 2006/95/EC, ICES-003 issue 5
Standards:	Class B, EN 300 328, EN 301 489-1, EN 301 489-3, EN 301 489-17, EN 60950- 1:2006+A11:2009+A1:2010+A12:2011

Software / System Requirements

Software Included:	HP Web JetAdmin, HP Embedded Web Server
-----------------------	--

OS Required:	HP-UX 10.20, SunSoft Solaris 2.5 or later, IBM AIX 3.2.5 or later, HP-UX 11.x, HP MPE/iX, Citrix Presentation Server, HP-UX 11i, Apple MacOS X 10.2, Apple MacOS X 10.3, Novell NetWare 5.1 or later, Microsoft Windows 7, Apple MacOS X 10.4 or later, Microsoft Windows Vista (32/64 bits), Microsoft Windows XP (32/64 bits), Microsoft Windows Server 2008 (32/64-bits), Microsoft Windows Server 2003 (32/64- bits), Red Hat Linux 7.x or later, SuSE Linux 8.x or later
-----------------	--

Dimensions & Weight

Width:	9.6 cm
Depth:	7.3 cm
Height:	2.1 cm
Weight:	80 g

Dimensions & Weight (Shipping)

Shipping Width:	22.4 cm
Shipping Depth:	15.2 cm
Shipping Height:	5.8 cm
Shipping Weight:	0.3 kg

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	45 °C
Humidity Range Operating:	15 - 95% (non- condensing)