

HP L7014 Retail Monitor - Head Only - LED monitor - 14"



14-10-2024

SKU	T6N31AA#ABB
Product Description:	HP L7014 Retail Monitor - Head Only - LED monitor - 14"
Device Type:	LED-backlit LCD monitor - 14"
Energy Class:	Class D
Power Consumption (On mode):	8 W
Panel Type:	TN
Aspect Ratio:	16:9
Native Resolution:	1366 x 768 at 60 Hz

General

Display Type:	LED-backlit LCD monitor / TFT active matrix
Energy Class:	Class D
Diagonal Size:	14"
Panel Type:	TN
Aspect Ratio:	16:9
Native Resolution:	1366 x 768 at 60 Hz
Pixel Pitch:	0.2265 mm
Pixel Per Inch:	112
Brightness:	200 cd/m ²
Contrast Ratio:	500:1
Colour Support:	14.4 million colours
Colour Gamut:	45%
Response Time:	16 ms (On/Off)
Vertical Refresh Rate:	50 - 76 Hz
Horizontal Refresh Rate:	24 - 80 kHz
Horizontal Viewing Angle:	90

Environmental Parameters

Min Operating Temperature:	5 °C
Max Operating Temperature:	35 °C
Humidity Range Operating:	20 - 80% (non-condensing)

Manufacturer Warranty

Service & Support:	Limited warranty - parts and labour - 3 years
--------------------	---

Dimensions & Weight (Shipping)

Shipping Width:	44.2 cm
Shipping Depth:	42.6 cm
Shipping Height:	31.6 cm
Shipping Weight:	2.8 kg

Dimensions & Weight

Dimensions & Weight Details:	Without stand - width: 33.98 cm - depth: 4.15 cm - height: 21.8 cm With stand - weight: 1.68 kg
------------------------------	---

Software / System Requirements

Included Software:	HP Display Assistant
OS Required:	Microsoft Windows 7 / 8 / 10

General

Vertical Viewing Angle: 60

Screen Coating: Anti-glare

Backlight Technology: LED backlight

Colour Temperature: 6500K

OSD Languages: Chinese (traditional), Chinese (simplified), Brazilian Portuguese, English, German, French, Italian, Portuguese, Spanish, Japanese

Features: Mercury free, arsenic-free glass

Colour: HP black, asteroid

Dimensions (WxDxH): 33.98 cm x 4.15 cm x 21.8 cm - without stand

Connectivity

Interfaces: DisplayPort (HDCP)

Mechanical

VESA Mounting Interface: 100 x 100 mm

Power

Input Voltage: AC 100/240 V (50/60 Hz)

Power Consumption (On mode): 8 W

Power Consumption SDR (On mode): 8 kWh/1000h

Power Consumption (Typical): 9.5 Watt

Power Consumption Stand by: 0.5 Watt

Miscellaneous

Features: VESA interface support

Backlight Life: 15,000 hours

Compliant Standards: Plug and Play, CSA, UL, VCCI, C-Tick, BSMI, cUL, WHQL, CB, CCC, PSB, FCC, C-ETL, ETL, KCC, ICES, cTUVus, MEPS, E-Standby, ERP, CECP, CEL, ISC, EPA 7.0

Localisation: English / Europe

