

HP L7014t Retail Touch Monitor - LED monitor - 14"



14-05-2024

SKU	T6N32AA#ABB
Product Description:	HP L7014t Retail Touch Monitor - LED monitor - 14"
Device Type:	LED-backlit LCD monitor - 14" - touchscreen
Energy Class:	Class D
Power Consumption (On mode):	8 W
Panel Type:	TN
Aspect Ratio:	16:9
Native Resolution:	1366 x 768 at 60 Hz

General

Display Type:	LED-backlit LCD monitor / TFT active matrix
Energy Class:	Class D
Diagonal Size:	14"
Panel Type:	TN
Aspect Ratio:	16:9
Native Resolution:	1366 x 768 at 60 Hz
Pixel Pitch:	0.2265 mm
Pixel Per Inch:	112
Brightness:	200 cd/m ²
Brightness w/touchscreen:	200 cd/m ²
Contrast Ratio:	350:1
Colour Support:	14.4 million colours
Colour Gamut:	45%
Response Time:	16 ms (On/Off)
Vertical Refresh Rate:	50 - 76 Hz
Horizontal Refresh Rate:	24 - 80 kHz
Horizontal Viewing Angle:	90

Environmental Parameters

Min Operating Temperature:	5 °C
Max Operating Temperature:	35 °C
Humidity Range Operating:	20 - 80% (non-condensing)

Manufacturer Warranty

Service & Support:	Limited warranty - parts and labour - 3 years
--------------------	---

Sustainability Information

ENERGY STAR Certified:	Yes
------------------------	-----

Dimensions & Weight (Shipping)

Shipping Width:	44.2 cm
Shipping Depth:	42.6 cm
Shipping Height:	31.6 cm
Shipping Weight:	2.8 kg

Software / System Requirements

Included Software:	HP Display Assistant
OS Required:	Microsoft Windows 7 / 8 / 10

Power

Produktdatablad genereret d. 30-04-2024 06:40.

Vær opmærksom på at priser og lagerstatus var gældende på genereringstidspunktet og dermed ikke kan garanteres.

General

Vertical Viewing Angle: 60

Screen Coating: Anti-glare

Backlight Technology: LED backlight

Colour Temperature: 6500K

OSD Languages: Chinese (traditional), Chinese (simplified), Brazilian Portuguese, English, German, French, Italian, Spanish, Dutch, Japanese

Features: HDCP, On-screen Digital Controls, Projected Capacitive Touch (PCT) technology, Mercury free, arsenic-free glass

Colour: HP black, asteroid

Dimensions (WxDxH): 33.98 cm x 4.15 cm x 21.8 cm - without stand

Weight: 1.7 kg

Input

Type: Touchscreen

KVM

Type: KVM switch

Connectivity

Interfaces: DisplayPort (HDCP) | Powered USB (12V)

Power

Input Voltage: AC 120/230 V (50/60 Hz)

Power Consumption (On mode): 8 W

Power Consumption SDR (On mode): 8 kWh/1000h

Power Consumption (Typical): 9.5 Watt

Power Consumption Stand by: 0.5 Watt

Miscellaneous

Features: VESA interface support

Cables Included: 1 x power cable - 1.83 m

Backlight Life: 15,000 hours

Compliant Standards: Plug and Play, CSA, UL, VCCI, C-Tick, BSMI, cUL, WHQL, CB, CCC, PSB, CSA NRTL/C, FCC, C-ETL, ETL, KCC, ICES, cTUVus, MEPS, E-Standby, ERP, CECP, CEL, ISC, EPA 7.0

Localisation: English / Europe

Mechanical

Display Position Adjustments: Tilt

