

HP L7016t Retail Touch Monitor - LED monitor - 15.6"



01-10-2024

SKU	V1X13AA#ABB
Product Description:	HP L7016t Retail Touch Monitor - LED monitor - 15.6"
Device Type:	LED-backlit LCD monitor - 15.6" - touchscreen
Energy Class:	Class F
Power Consumption (On mode):	13 W
Panel Type:	TN
Aspect Ratio:	16:9
Native Resolution:	1366 x 768 at 60 Hz

General

Display Type:	LED-backlit LCD monitor / TFT active matrix
Energy Class:	Class F
Diagonal Size:	15.6"
Panel Type:	TN
Aspect Ratio:	16:9
Native Resolution:	1366 x 768 at 60 Hz
Pixel Pitch:	0.252 mm
Pixel Per Inch:	100
Brightness:	360 cd/m ²
Brightness w/touchscreen:	360 cd/m ²
Contrast Ratio:	500:1
Colour Support:	16.2 million colours
Colour Gamut:	62%
Response Time:	8 ms (On/Off)
Vertical Refresh Rate:	50 - 76 Hz
Horizontal Refresh Rate:	24 - 80 kHz
Horizontal Viewing Angle:	170

Environmental Parameters

Min Operating Temperature:	5 °C
Max Operating Temperature:	35 °C
Humidity Range Operating:	20 - 80% (non-condensing)

Manufacturer Warranty

Service & Support:	Limited warranty - parts and labour - 3 years
--------------------	---

Dimensions & Weight (Shipping)

Shipping Width:	47.8 cm
Shipping Depth:	33 cm
Shipping Height:	14 cm
Shipping Weight:	4.5 kg

Dimensions & Weight

Dimensions & Weight Details:	Without stand - width: 39.73 cm - depth: 4.5 cm - height: 25.14 cm With stand - weight: 3 kg
------------------------------	--

Software / System Requirements

Included Software:	HP Display Assistant
OS Required:	Microsoft Windows 7 / 8 / 10

Produktdatablad genereret d. 08-09-2024 05:00.

Vær opmærksom på at priser og lagerstatus var gældende på genereringstidspunktet og dermed ikke kan garanteres.

General

Vertical Viewing Angle:	160
Screen Coating:	Anti-glare
Backlight Technology:	LED backlight
Colour Temperature:	6500K
OSD Languages:	Chinese (traditional), Chinese (simplified), Brazilian Portuguese, English, German, French, Italian, Spanish, Dutch, Japanese
Features:	HDCP, On-screen Digital Controls, Projected Capacitive Touch (PCT) technology, Mercury free, arsenic-free glass
Colour:	HP black, asteroid
Dimensions (WxDxH):	39.73 cm x 4.5 cm x 25.14 cm - without stand

Input

Type:	Touchscreen
-------	-------------

Connectivity

Interfaces:	DisplayPort (HDCP) ; Powered USB (12V)
-------------	--

Mechanical

Display Position Adjustments:	Tilt
Tilt Angle:	-5/+135
VESA Mounting Interface:	100 x 100 mm

Power

Input Voltage:	AC 120/230 V (50/60 Hz)
Power Consumption (On mode):	13 W
Power Consumption SDR (On mode):	13 kWh/1000h
Power Consumption (Typical):	14 Watt
Power Consumption Stand by:	0.5 Watt

Miscellaneous

Cables Included:	1 x power cable - 1.83 m
Backlight Life:	50,000 hours
Compliant Standards:	Plug and Play, CSA, UL, VCCI, C-Tick, BSMI, cUL, WHQL, CB, CCC, PSB, CSA NRTL/C, FCC, C-ETL, ETL, KCC, ICES, cTUVus, MEPS, E-Standby, ERP, CECP, CEL, ISC, EPA 7.0
Localisation:	English / Europe