

HP Mini-in-One 24 - LED monitor - Full HD (1080p) - 23.8"



Not in stock

SKU	7AX23AA#ABB
Product Description:	HP Mini-in-One 24 - LED monitor - Full HD (1080p) - 23.8"
Device Type:	LED-backlit LCD monitor - 23.8"
Energy Label QR Code URL:	https://eprel.ec.europa.eu/qr/298059
Energy Class:	Class E
Power Consumption (On mode):	17.8 W
Features:	USB 3.1 Gen 1 hub
Panel Type:	IPS

General

Display Type: LED-backlit LCD monitor / TFT active matrix

Energy Label QR Code URL: <https://eprel.ec.europa.eu/qr/298059>

Energy Class: Class E

Diagonal Size: 23.8"

Built-in Devices: USB 3.1 Gen 1 hub

Panel Type: IPS

Aspect Ratio: 16:9

Native Resolution: Full HD (1080p) 1920 x 1080 at 60 Hz

Pixel Pitch: 0.2745 mm

Pixel Per Inch: 93.24

Brightness: 250 cd/m²

Contrast Ratio: 1000:1 / 800000:1 (dynamic)

Colour Gamut: 72% NTSC

Response Time: 14 ms (grey-to-grey), 5 ms (overdrive)

Vertical Refresh Rate: 50 - 60 Hz

Horizontal Refresh Rate: 30 - 80 kHz

Environmental Parameters

Min Operating Temperature: 5 °C

Max Operating Temperature: 35 °C

Humidity Range Operating: 20 - 80%

Sustainability Information

ENERGY STAR Certified: Yes

Dimensions & Weight (Shipping)

Shipping Width: 65 cm

Shipping Depth: 47.3 cm

Shipping Height: 31.5 cm

Shipping Weight: 12.78 kg

Dimensions & Weight

Dimensions & Weight Details: With stand - width: 53.96 cm - depth: 24.2 cm - height: 50.38 cm - weight: 7.2 kg ; Without stand - width: 53.96 cm - depth: 7.5 cm - height: 36.76 cm - weight: 4.06 kg

Power

Input Voltage: AC 120/230 V (50/60 Hz)

Power Consumption (On mode): 17.8 W

General

Horizontal Viewing Angle: 178

Vertical Viewing Angle: 178

Screen Coating: Anti-glare

Backlight Technology: LED backlight

Colour Temperature: 6500K

OSD Languages: Chinese (traditional), Chinese (simplified), English, German, French, Italian, Portuguese, Spanish, Dutch, Japanese

Features: Low Blue Light Mode, Flicker Free technology, Mercury free, arsenic-free glass, 3-sided micro-edge, 72% NTSC colour gamut

Colour: Black, silver (stand)

Dimensions (WxDxH): 53.96 cm x 24.2 cm x 50.38 cm - with stand

Weight: 7.2 kg

Audio

Type: Speakers - stereo

Output Power / Channel: 2 Watt

Connectivity

Interfaces: DisplayPort (HDCP) ; USB 3.1 Gen 1 upstream (Type B) ; 6 x USB 3.1 Gen 1 downstream (Type A) ; USB-C 3.1 Gen 1 (HDCP) ; Audio line-in ; Audio line-out

Mechanical

Display Position Adjustments: Height, pivot (rotation), swivel, tilt

Tilt Angle: 180

Swivel Angle: 90

Rotation Angle: 90

Power

Power Consumption SDR (On mode): 17.8 kWh/1000h

Power Consumption (Typical): 50 Watt

Power Consumption Stand by: 0.5 Watt

Miscellaneous

Features: Security lock slot (cable lock sold separately)

Backlight Life: 30,000 hours

Compliant Standards: Plug and Play, CSA, UL, VCCI, BSMI, NOM, TUV S, WHQL, CB, CCC, PSB, FCC, ISO 9241-307, KCC, WEEE, MEPS, KC, CECP, CEL, EAC, ISC, SEPA, low halogen, ICE

Localisation: English / Europe

Security Slot Type: Kensington security slot

Mechanical

Height Adjustment: 150 mm

VESA Mounting Interface: 100 x 100 mm

