

HP P34hc G4 - P-Series - LED monitor - curved - 34"



In Stock(366)

SKU	21Y56AA#ABB
Product Description:	HP P34hc G4 - P-Series - LED monitor - curved - 34"
Device Type:	LED-backlit LCD monitor - 34"
Energy Class:	Class G
Power Consumption (On mode):	34 W
Curved Screen:	Yes
Features:	USB 3.2 Gen 1 hub, USB PD 65 Watt
Panel Type:	VA

General

Display Type:	LED-backlit LCD monitor / TFT active matrix
Energy Class:	Class G
Diagonal Size:	34"
Curved Screen:	Yes (1500R)
Built-in Devices:	USB 3.2 Gen 1 hub
USB Power Delivery:	65 Watt
Panel Type:	VA
Aspect Ratio:	21:9
Native Resolution:	WQHD 3440 x 1440 at 60 Hz
Pixel Pitch:	0.23175 mm
Pixel Per Inch:	110
Brightness:	250 cd/m²
Contrast Ratio:	3500:1 / 50000000:1 (dynamic)
Colour Gamut:	85% NTSC
Response Time:	5 ms (grey-to-grey with overdrive)
Vertical Refresh Rate:	48 - 100 Hz

Environmental Parameters

Min Operating Temperature:	5 °C
Max Operating Temperature:	35 °C
Humidity Range Operating:	20 - 80% (non-condensing)

Manufacturer Warranty

Service & Support:	Limited warranty - parts and labour - 3 years
--------------------	---

Sustainability Information

TCO Certified:	TCO Certified Displays 8, TCO Certified Edge Displays
ENERGY STAR Certified:	Yes

Dimensions & Weight (Shipping)

Shipping Width:	95 cm
Shipping Depth:	22.5 cm
Shipping Height:	48 cm
Shipping Weight:	16.7 kg

Dimensions & Weight

General

Horizontal Refresh Rate: 30 - 160 kHz

Horizontal Viewing Angle: 178

Vertical Viewing Angle: 178

Screen Coating: Anti-glare, 3H Hard Coating, Haze 25%

Backlight Technology: LED backlight

Colour Temperature: 6500K

OSD Languages: Chinese (traditional), Chinese (simplified), English, German, French, Italian, Portuguese, Spanish, Dutch, Japanese

Features: Low Blue Light Mode, Flicker Free technology, Mercury free, arsenic free, 3-sided micro-edge, 8-bit Colour Depth, edge-lit LED backlight

Colour: Black

Dimensions (WxDxH): 80.94 cm x 23.49 cm x 51.8 cm - with stand

Weight: 10.51 kg

Audio

Type: Speakers - stereo

Output Power / Channel: 3 Watt

Connectivity

Interfaces: HDMI (HDCP) | DisplayPort 1.2 (HDCP) | Audio line-out | USB-C upstream/DisplayPort Alt Mode with Power Delivery (HDCP / power up to 65W) | 4 x USB 3.2 Gen 1 | USB (Type B) | KVM

Mechanical

Display Position Adjustments: Height, tilt

Tilt Angle: -5/+21

Height Adjustment: 100 mm

Dimensions & Weight

Dimensions & Weight Details: With stand - width: 80.94 cm - depth: 23.49 cm - height: 51.8 cm - weight: 10.51 kg | Without stand - width: 80.94 cm - depth: 11.21 cm - height: 36.69 cm - weight: 7.85 kg

Software / System Requirements

Included Software: HP Display Center

Power

Input Voltage: AC 120/230 V (50/60 Hz)

Power Consumption (On mode): 34 W

Power Consumption SDR (On mode): 39 kWh/1000h

Power Consumption (Typical): 48 Watt

Power Consumption Stand by: 0.5 Watt

Miscellaneous

Features: Security lock slot (cable lock sold separately), detachable stand, VESA interface support

Cables Included: 1 x HDMI cable - 1.8 m | 1 x DisplayPort cable - 1.8 m | 1 x USB-C to USB-C cable - 1.8 m

Mounting Kit: Included

Backlight Life: 30,000 hours

Compliant Standards: TUV, VCCI, GS, NOM, WHQL, CB, CCC, FCC, ISO 9241-307, KCC, WEEE, cTUVus, KC, CEL, EPA, EAC, RCM, BIS, low halogen, DisplayPort 1.2, ICE, KES

Localisation: English / Europe

Security Slot Type: Kensington security slot

Mechanical

VESA Mounting Interface:

100 x 100 mm

