

# HP ScanJet Enterprise Flow N7000 snw1 - document scanner - desktop - USB 3.0, LAN, Wi-Fi(n)



Not in stock

|                              |                                                                                             |
|------------------------------|---------------------------------------------------------------------------------------------|
| SKU                          | 6FW10A#B19                                                                                  |
| Product Description:         | HP ScanJet Enterprise Flow N7000 snw1 - document scanner - desktop - USB 3.0, LAN, Wi-Fi(n) |
| Device Type:                 | Document scanner - desktop                                                                  |
| Interface Type:              | USB 3.0, LAN, Wi-Fi(n)                                                                      |
| Scanning Sensor Type:        | CMOS / CIS                                                                                  |
| Light Source:                | LED                                                                                         |
| Additional Functions:        | Scan to cloud, scan to USB, scan to email                                                   |
| Max Supported Document Size: | 216 x 3100 mm                                                                               |

## General

|                              |                                                    |
|------------------------------|----------------------------------------------------|
| Type:                        | Document scanner - desktop                         |
| Interface Type:              | USB 3.0, LAN, Wi-Fi(n)                             |
| Additional Functions:        | Scan to cloud, scan to USB, scan to email          |
| Max Supported Document Size: | 216 x 3100 mm                                      |
| Localisation:                | English, German, French, Italian, Spanish / Europe |

## Environmental Parameters

|                            |          |
|----------------------------|----------|
| Min Operating Temperature: | 10 °C    |
| Max Operating Temperature: | 35 °C    |
| Humidity Range Operating:  | 10 - 80% |

## Manufacturer Warranty

|                    |                                                                                                                         |
|--------------------|-------------------------------------------------------------------------------------------------------------------------|
| Service & Support: | Limited warranty - 1 year   Technical support - phone consulting - 1 year   Product info support - web support - 1 year |
|--------------------|-------------------------------------------------------------------------------------------------------------------------|

## Scanner

|                          |                               |
|--------------------------|-------------------------------|
| Input Type:              | Colour                        |
| Grayscale Depth:         | 8-bit (256 grey levels)       |
| Colour Depth:            | 48-bit colour                 |
| Colour Depth (External): | 24-bit (16.7 million colours) |
| Optical Resolution:      | 600 dpi x 600 dpi             |
| Scan Mode:               | Single-pass                   |
| Automatic Duplexing:     | Yes                           |

## Dimensions & Weight (Shipping)

|                  |         |
|------------------|---------|
| Shipping Width:  | 39.7 cm |
| Shipping Depth:  | 24.8 cm |
| Shipping Height: | 30.3 cm |
| Shipping Weight: | 5.6 kg  |

## Dimensions & Weight

|         |         |
|---------|---------|
| Width:  | 31 cm   |
| Depth:  | 19.8 cm |
| Height: | 19 cm   |
| Weight: | 4 kg    |

## Software / System Requirements

## Scanner

|                                 |                                                                                                                                                                                                         |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Scanning Sensor Type:           | CMOS / CIS                                                                                                                                                                                              |
| Bulb / Light Source Type:       | LED                                                                                                                                                                                                     |
| Max Document Scan Speed B/W:    | 75 ppm                                                                                                                                                                                                  |
| Max Document Scan Speed Colour: | 75 ppm                                                                                                                                                                                                  |
| Duty Cycle:                     | 7500 scans per day                                                                                                                                                                                      |
| Scanner Speed Details:          | 75 ppm - black & white - A4 / Letter - 300 dpi ; 75 ppm - colour - A4 / Letter - 300 dpi ; 150 ipm - duplex - black & white - A4 / Letter - 300 dpi ; 150 ipm - duplex - colour - A4 / Letter - 300 dpi |
| Scanner Features:               | Touch screen, Auto Crop, auto power off, edge cleanup                                                                                                                                                   |
| Scan File Formats:              | BMP, JPEG, PNG, TIFF, PDF, RTF, TXT                                                                                                                                                                     |
| Compliant Standards:            | TWAIN, ISIS, WIA                                                                                                                                                                                        |

## Software / System Requirements

|                              |                                                                                            |
|------------------------------|--------------------------------------------------------------------------------------------|
| Software Included:           | Readiris Pro, Cardiris Pro                                                                 |
| OS Required:                 | Microsoft Windows 7, Microsoft Windows Vista, Microsoft Windows XP SP3 or later, Windows 8 |
| System Requirements Details: | Windows XP/7/8/8.1 - RAM 2 GB (USB) ; MacOS - RAM 1 GB (USB)                               |

## Power

|                                          |                         |
|------------------------------------------|-------------------------|
| Power Device:                            | External power adapter  |
| Voltage Required:                        | AC 120/230 V (50/60 Hz) |
| Power Consumption Operational (Standby): | 38 Watt                 |
| Power Consumption Stand by:              | 5.8 Watt                |
| Power Consumption Sleep:                 | 1.9 Watt                |

## Environmental Standards

|                        |              |
|------------------------|--------------|
| EPEAT Compliant:       | EPEAT Silver |
| ENERGY STAR Certified: | Yes          |

## Miscellaneous

|                      |                                                                                                                                                                                                                                                                                                                                                                           |
|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Compliant Standards: | RoHS, FCC CFR47 Part 15 B, CECP, GB 9254-2008, EN 62479:2010, IEC 62471:2006, EN 62471:2008, GB 4943-2011, GB 17625.1-2012, EN 61000-3-3:2013, EN 55024:2010, CISPR 22:2008, EN 61000-3-2:2014, IEC 62479:2010, ICES-003 issue 6, IEC/EN60950-1:2006 +A11:2009 +A1:2010 +A12:2011 +A2:2013, CISPR 32:2012, IEC 60950-1:2005 (ed.2)+A1:2009+A2:2013, EN 55032:2012 Class B |
|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

## Expansion / Connectivity

|                     |                       |
|---------------------|-----------------------|
| Interfaces Details: | USB 3.0 ; Gigabit LAN |
|---------------------|-----------------------|

## Memory

|               |      |
|---------------|------|
| Flash Memory: | 1 GB |
|---------------|------|

## Media Handling

## Media Handling

|                                  |                             |
|----------------------------------|-----------------------------|
| Max Document Size:               | 216 mm x 3100 mm            |
| Supported Document Type:         | Business card, plastic card |
| Supported Document Size Details: | ADF - up to 216 x 3100 mm   |
| Document Feeder Type:            | Automatic                   |
| Document Storage Capacity:       | 80 sheets                   |

