

HP Z24m G3 - LED monitor - 23.8" - HDR



In Stock(49)

SKU	4Q8N9AA#ABB
Product Description:	HP Z24m G3 - LED monitor - 23.8" - HDR
Device Type:	LED-backlit LCD monitor - 23.8"
Energy Class:	Class F
Features:	USB 3.2 Gen 1 hub, USB PD 100 Watt
Panel Type:	IPS
Aspect Ratio:	16:9
Native Resolution:	QHD 2560 x 1440 at 90 Hz

General

Display Type:	LED-backlit LCD monitor / TFT active matrix
Energy Class:	Class F
Energy Class (HDR):	Class G
Diagonal Size:	23.8"
Built-in Devices:	USB 3.2 Gen 1 hub
USB Power Delivery:	100 Watt
Panel Type:	IPS
Aspect Ratio:	16:9
Native Resolution:	QHD 2560 x 1440 at 90 Hz
Pixel Pitch:	0.2058 mm
Brightness:	400 cd/m ²
Contrast Ratio:	1000:1
HDR Certification:	DisplayHDR 400
Response Time:	5 ms (grey-to-grey with overdrive)
Horizontal Refresh Rate:	30 - 140 kHz

Environmental Parameters

Min Operating Temperature:	5 °C
Max Operating Temperature:	35 °C
Humidity Range Operating:	20 - 80% (non-condensing)

Manufacturer Warranty

Service & Support:	Limited warranty - parts and labour - 3 years
--------------------	---

Dimensions & Weight (Shipping)

Shipping Width:	62.5 cm
Shipping Depth:	14.1 cm
Shipping Height:	38.7 cm
Shipping Weight:	8.2 kg

Dimensions & Weight

Dimensions & Weight Details:	With stand - width: 53.83 cm - depth: 19.5 cm - height: 48.93 cm - weight: 5.7 kg Without stand - width: 53.83 cm - depth: 4.84 cm - height: 31.17 cm
------------------------------	---

Software / System Requirements

Included Software:	HP Display Assistant
--------------------	----------------------

Power

Input Voltage:	(50/60 Hz)
----------------	------------

Produktdatablad genereret d. 16-09-2024 21:37.

Vær opmærksom på at priser og lagerstatus var gældende på genereringstidspunktet og dermed ikke kan garanteres.

General

Horizontal Viewing Angle: 178

Vertical Viewing Angle: 178

Screen Coating: Anti-glare, 3H Hard Coating

Backlight Technology: LED backlight

Features: Flicker Free technology, Factory Calibration, Low Blue Light technology, 10-bit Colour Depth, edge-lit LED backlight, 4-sided micro-edge

Dimensions (WxDxH): 53.83 cm x 19.5 cm x 48.93 cm - with stand

Weight: 5.7 kg

Connectivity

Interfaces: HDMI (HDCP) ; DisplayPort 1.4 (HDCP) ; DisplayPort output (HDCP) ; USB-C 3.1 Gen 2 upstream/DisplayPort 1.4 Alt Mode (power up to 100W) ; 4 x USB 3.2 Gen 1

Mechanical

Display Position Adjustments: Height, pivot (rotation), swivel, tilt

Tilt Angle: -5/+20

Swivel Angle: 90

Rotation Angle: 180

Height Adjustment: 150 mm

VESA Mounting Interface: 100 x 100 mm

Power

Power Consumption SDR (On mode): 21.5 kWh/1000h

Power Consumption HDR (On mode): 26.6 kWh/1000h

Power Consumption (Typical): 38 Watt

Power Consumption (Max): 170 Watt

Power Consumption Stand by: 0.5 Watt

Miscellaneous

Features: Security lock slot (cable lock sold separately), detachable stand, VESA interface support

Included Accessories: Cable management cover, mount adapter

Cables Included: 1 x HDMI cable ; 1 x DisplayPort cable

Mounting Kit: Included

Compliant Standards: VCCI, BSMI, GS, NOM, CB, CCC, PSB, ISO 9241-307, KCC, WEEE, cTUVus, KC, ERP, CECP, CEL, EAC, ISC, SEPA, BIS, low halogen, UAE, Ukraine Energy Label

Localisation: English / Europe

Security Slot Type: Kensington security slot