

HP Z27k G3 - LED monitor - 4K - 27"



In Stock(6)

SKU	1B9TOAA#ABB
Product Description:	HP Z27k G3 - LED monitor - 4K - 27"
Device Type:	LED-backlit LCD monitor - 27"
Energy Class:	Class G
Power Consumption (On mode):	29.1 W
Features:	USB 3.2 Gen 1 hub, USB PD 100 Watt
Panel Type:	IPS
Aspect Ratio:	16:9

General

Display Type:	LED-backlit LCD monitor / TFT active matrix
Energy Class:	Class G
Diagonal Size:	27"
Built-in Devices:	USB 3.2 Gen 1 hub
USB Power Delivery:	100 Watt
Panel Type:	IPS
Aspect Ratio:	16:9
Native Resolution:	4K 3840 x 2160 at 60 Hz
Pixel Pitch:	0.155 mm
Pixel Per Inch:	163
Brightness:	350 cd/m²
Contrast Ratio:	1000:1 / 10000000:1 (dynamic)
Colour Gamut:	99% sRGB
Response Time:	5 ms (grey-to-grey with overdrive)

Environmental Parameters

Min Operating Temperature:	5 °C
Max Operating Temperature:	35 °C
Humidity Range Operating:	20 - 80% (non-condensing)

Sustainability Information

TCO Certified:	TCO Certified Displays 8, TCO Certified Edge Displays
ENERGY STAR Certified:	Yes

Dimensions & Weight (Shipping)

Shipping Width:	69.8 cm
Shipping Depth:	42.3 cm
Shipping Height:	16.3 cm
Shipping Weight:	9.4 kg

Dimensions & Weight

Dimensions & Weight Details:	With stand - width: 61.23 cm - depth: 20.5 cm - height: 53.04 cm - weight: 6.2 kg Without stand - width: 61.23 cm - depth: 6.35 cm - height: 35.61 cm
------------------------------	---

Power

General

Vertical Refresh Rate: 50 - 60 Hz

Horizontal Refresh Rate: 30 - 80 kHz

Horizontal Viewing Angle: 178

Vertical Viewing Angle: 178

Screen Coating: Anti-glare, 3H Hard Coating

Backlight Technology: LED backlight

Features: Low Blue Light Mode, Flicker Free technology, Mercury free, arsenic-free glass, 10-bit Colour Depth, edge-lit LED backlight, 4-sided micro-edge, 99% sRGB colour gamut

Dimensions (WxDxH): 61.23 cm x 20.5 cm x 53.04 cm - with stand

Weight: 6.2 kg

Connectivity

Interfaces: DisplayPort 1.4 | 4 x USB 3.2 Gen 1 downstream | USB-C upstream/DisplayPort Alt Mode with Power Delivery (power up to 100W) | DisplayPort output | HDMI

Mechanical

Display Position Adjustments: Height, pivot (rotation), swivel, tilt

Tilt Angle: -5/+20

Swivel Angle: 90

Rotation Angle: 180

Height Adjustment: 150 mm

VESA Mounting Interface: 100 x 100 mm

Power

Input Voltage: AC 120/230 V (50/60 Hz)

Power Consumption (On mode): 29.1 W

Power Consumption SDR (On mode): 29.1 kWh/1000h

Power Consumption (Typical): 42 Watt

Power Consumption Stand by: 0.5 Watt

Miscellaneous

Features: Security lock slot (cable lock sold separately), detachable stand, VESA interface support

Included Accessories: VESA bracket

Cables Included: 1 x DisplayPort cable | 1 x USB-C to USB-C cable

Compliant Standards: VCCI, BSMI, GS, NOM, TUV S, CB, CCC, PSB, FCC, ISO 9241-307, KCC, WEEE, cTUVus, KC, CECP, CEL, EAC, SEPA, BIS, low halogen, UAE, Australian-New Zealand MEPS, Vietnam MEPS, Ukraine Energy Label

Localisation: English / Europe

Security Slot Type: Kensington security slot