

Intel Server System R1208WTTGSR - rack-mountable - no CPU - 0 GB - no HDD



06-05-2024

SKU	R1208WTTGSR
Product Description:	Intel Server System R1208WTTGSR - rack-mountable - no CPU - 0 GB - no HDD
Type:	Server - rack-mountable
Height (Rack Units):	1U
Server Scalability:	2-way
Processor:	No CPU
Processor Socket:	LGA2011-v3 Socket
RAM:	0 GB (installed) / 1536 GB (max) - DDR4 SDRAM - ECC

General

Type:	Server
Product Form Factor:	Rack-mountable - 1U
Embedded Security:	Trusted Platform Module (TPM 2.0) Security Chip
Server Scalability:	2-way
Front Accessible Bays Qty:	8
Hot-Swap Bays Qty:	8

Processor / Chipset

CPU:	No CPU
Max CPU Qty:	2
CPU Upgradability:	Upgradable
CPU Socket:	LGA2011-v3 Socket
Chipset Type:	Intel C612

RAM

Installed Size:	0 GB / 1536 GB (max)
Technology:	DDR4 SDRAM - ECC
Form Factor:	DIMM 288-pin

Dimensions & Weight

Width:	43 cm
Depth:	71 cm
Height:	4.37 cm

Manufacturer Warranty

Service & Support:	Limited warranty - 3 years
--------------------	----------------------------

Power

Device Type:	Power supply - hot-plug
Power Redundancy:	Optional
Power Redundancy Scheme:	1+1 (with optional power supply)
Installed Qty:	1
Max Supported Qty:	2
Voltage Required:	AC 120/230 V (50/60 Hz)
Power Provided:	750 Watt

Miscellaneous

Included Accessories:	2 x CPU Heatsink, 2 x riser cards
Cables Included:	Mini SAS HD cable (2 pcs.)

RAM

Slots: 24 (Total) / 24 (empty)

Hard Drive

Type: No HDD

Storage Controller

Type: 1 x RAID

Controller Interface Type: SATA 6Gb/s / SAS 12Gb/s

Channel Qty: 10

RAID Level: RAID 0, RAID 1, RAID 10

Optical Storage

Type: No optical drive

Monitor

Monitor Type: None.

Graphics Controller

Type: Integrated

Video Interfaces: VGA

Expansion / Connectivity

Bays: 8 (total) / 8 (free) x hot-swap 2.5"

Slots: 2 (total) / 2 (free) x CPU ; 24 (total) / 24 (free) x DIMM 288-pin ; 1 (total) / 1 (free) x PCIe 3.0 x4 ; 1 (total) / 1 (free) x PCIe 3.0 x8 ; 2 (total) / 2 (free) x PCIe 3.0 x16

Interfaces: 1 x VGA ; 8 x USB 3.0 ; 2 x LAN (10Gigabit Ethernet) - RJ-45 ; 2 x serial - RJ-45

Networking

Ethernet Ports: 2 x 10 Gigabit Ethernet

Ethernet Controller: Intel X540

Data Link Protocol: Ethernet, Fast Ethernet, Gigabit Ethernet, 10 Gigabit Ethernet

Remote Management Protocol: IPMI 2.0

Remote Management Controller: Emulex Pilot 3 iBMC

