

Intel Server System R1304GL4DS9 - rack-mountable - no CPU - 0 GB - no HDD



16-05-2024

SKU	R1304GL4DS9
Product Description:	Intel Server System R1304GL4DS9 - rack-mountable - no CPU - 0 GB - no HDD
Type:	Server - rack-mountable
Height (Rack Units):	1U
Server Scalability:	2-way
Processor:	No CPU
Processor Socket:	LGA2011 Socket
RAM:	0 GB (installed) / 512 GB (max) - DDR3 SDRAM - ECC

General

Type:	Server
Product Form Factor:	Rack-mountable - 1U
Server Scalability:	2-way
Internal Bays Qty:	4
Front Accessible Bays Qty:	1

Processor / Chipset

CPU:	No CPU
Max CPU Qty:	2
CPU Upgradability:	Upgradable
CPU Socket:	LGA2011 Socket
Chipset Type:	Intel C600-A

RAM

Installed Size:	0 GB / 512 GB (max)
Technology:	DDR3 SDRAM - ECC
Form Factor:	DIMM 240-pin
Slots:	16 (Total) / 16 (empty)

Dimensions & Weight

Width:	43.8 cm
Depth:	55.3 cm
Height:	4.5 cm

Manufacturer Warranty

Service & Support:	Limited warranty - 3 years
--------------------	----------------------------

Power

Device Type:	Power supply
Power Redundancy:	Yes
Power Redundancy Scheme:	1+1
Installed Qty:	2
Max Supported Qty:	2
Voltage Required:	AC 120/230 V (50/60 Hz)
Power Provided:	460 Watt

Miscellaneous

Included Accessories:	2 x CPU Heatsink
Cables Included:	Serial ATA / SAS cable (2 pcs.)

Expansion / Connectivity

RAM

Features:	Unbuffered, registered, quad channel memory architecture, Load-Reduced DIMM (LRDIMM)
-----------	--

Hard Drive

Type:	No HDD
-------	--------

Storage Controller

Type:	1 x SATA - integrated
Controller Interface Type:	SATA 6Gb/s
Channel Qty:	2

Storage Controller (2nd)

Type:	1 x SAS - integrated
Controller Interface Type:	SATA 3Gb/s / SAS
Channel Qty:	8
RAID Level:	RAID 0, RAID 1, RAID 10

Optical Storage

Type:	No optical drive
-------	------------------

Monitor

Monitor Type:	None.
---------------	-------

Expansion / Connectivity

Bays:	4 (total) / 4 (free) x internal 3.5" ; 1 (total) / 1 (free) x external 5.25" Slim Line
Slots:	2 (total) / 2 (free) x CPU ; 16 (total) / 16 (free) x DIMM 240-pin ; 2 (total) / 2 (free) x PCIe 3.0 x16
Interfaces:	1 x VGA ; 2 x USB 2.0 ; 1 x serial ; 4 x LAN (Gigabit Ethernet) ; 1 x management

Networking

Type:	Integrated
Ethernet Ports:	4 x Gigabit Ethernet
Data Link Protocol:	Ethernet, Fast Ethernet, Gigabit Ethernet
Remote Management Protocol:	IPMI 2.0

Graphics Controller

Type:	Integrated
Video Memory:	16 MB DDR3 SDRAM
Video Interfaces:	VGA

