

Intel Server System R1304RPOSHBN - rack-mountable - no CPU

- 0 GB - no HDD



23-05-2024

SKU	R1304RPOSHBN
Product Description:	Intel Server System R1304RPOSHBN - rack-mountable - no CPU - 0 GB - no HDD
Type:	Server - rack-mountable
Height (Rack Units):	1U
Server Scalability:	1-way
Processor:	No CPU
Processor Socket:	LGA1150 Socket
RAM:	0 GB (installed) / 32 GB (max) - DDR3 SDRAM - ECC

General

Type:	Server
Product Form Factor:	Rack-mountable - 1U
Server Scalability:	1-way
Front Accessible Bays Qty:	1
Hot-Swap Bays Qty:	4

Processor / Chipset

CPU:	No CPU
Max CPU Qty:	1
CPU Upgradability:	Upgradable
CPU Socket:	LGA1150 Socket
Chipset Type:	Intel C224

RAM

Installed Size:	0 GB / 32 GB (max)
Technology:	DDR3 SDRAM - ECC
Form Factor:	DIMM 240-pin
Slots:	4 (Total) / 4 (empty)
Features:	Unbuffered, Load-Reduced DIMM (LRDIMM)

Dimensions & Weight

Width:	43.8 cm
Depth:	55.4 cm
Height:	4.5 cm

Manufacturer Warranty

Service & Support:	Limited warranty - 3 years
--------------------	----------------------------

Power

Device Type:	Power supply
Voltage Required:	AC 120/230 V (50/60 Hz)
Power Provided:	350 Watt

Miscellaneous

Included Accessories:	CPU Heatsink
Cables Included:	Serial ATA cable (4 pcs.) ; IDE cable

Expansion / Connectivity

Bays:	4 (total) / 4 (free) x hot-swap 3.5" ; 1 (total) / 1 (free) x external 5.25" Slim Line
-------	--

Hard Drive

Type: No HDD

Storage Controller

Type: 1 x SATA - integrated

Controller Interface Type: SATA 6Gb/s

Channel Qty: 4

Storage Controller (2nd)

Type: 1 x SATA - integrated

Controller Interface Type: SATA 3Gb/s

Channel Qty: 2

Optical Storage

Type: No optical drive

Monitor

Monitor Type: None.

Expansion / Connectivity

Slots: 1 (total) / 1 (free) x CPU ; 4 (total) / 4 (free) x DIMM 240-pin ; 1 (total) / 1 (free) x PCIe 3.0 x16 (x8 mode)

Interfaces: 1 x VGA ; 1 x serial ; 2 x LAN (Gigabit Ethernet) ; 4 x USB 2.0 (2 front, 2 rear) ; 2 x USB 3.0

Networking

Type: Integrated

Ethernet Ports: 2 x Gigabit Ethernet

Ethernet Controller: 2 x Intel I210-AT

Data Link Protocol: Ethernet, Fast Ethernet, Gigabit Ethernet

Remote Management Protocol: IPMI 2.0

Graphics Controller

Type: Integrated

Video Memory: 16 MB DDR3 SDRAM

Video Interfaces: VGA

