

Intel Server System R1304WFOZSR - rack-mountable - no CPU - 0 GB - no HDD



Not in stock

SKU	R1304WFOZSR
Product Description:	Intel Server System R1304WFOZSR - rack-mountable - no CPU - 0 GB - no HDD
Type:	Server - rack-mountable
Height (Rack Units):	1U
Server Scalability:	2-way
Processor:	No CPU
Processor Socket:	Socket P
Processor Main Features:	Intel Virtualization Technology for Directed I/O

General

Type:	Server
Product Form Factor:	Rack-mountable - 1U
Embedded Security:	Trusted Platform Module (TPM 2.0) Security Chip
Server Scalability:	2-way
Internal Bays Qty:	2
Front Accessible Bays Qty:	4
Hot-Swap Bays Qty:	4

Processor / Chipset

CPU:	No CPU
Max CPU Qty:	2
CPU Upgradability:	Upgradable
Processor Main Features:	Intel Virtualization Technology for Directed I/O
CPU Socket:	Socket P
Chipset Type:	Intel C624

RAM

Dimensions & Weight (Shipping)

Shipping Width:	57.7 cm
Shipping Depth:	98.3 cm
Shipping Height:	25.9 cm

Dimensions & Weight

Width:	43 cm
Depth:	71 cm
Height:	4.37 cm

Manufacturer Warranty

Service & Support:	Limited warranty - 3 years
--------------------	----------------------------

Power

Device Type:	Power supply - hot-plug
Power Redundancy:	Optional
Power Redundancy Scheme:	1+1 (with optional power supply)
Installed Qty:	1
Max Supported Qty:	2
Power Provided:	1300 Watt
80 PLUS Certification:	80 PLUS Titanium

RAM

Installed Size:	0 GB / 6 TB (max)
Technology:	DDR4 SDRAM - ECC
Form Factor:	DIMM 288-pin
Slots:	24 (Total) / 24 (empty)
Features:	Registered, Load-Reduced DIMM (LRDIMM), supports Intel Optane DC Persistent Memory (DCPMM)

Hard Drive

Type:	No HDD
Features:	Intel Rapid Storage Technology

Storage Controller

Type:	RAID
Controller Interface Type:	SATA 6Gb/s
Channel Qty:	10
RAID Level:	RAID 0, RAID 1, RAID 10

Optical Storage

Type:	No optical drive
-------	------------------

Monitor

Monitor Type:	None.
---------------	-------

Networking

Ethernet Ports:	2 x 10 Gigabit Ethernet
Data Link Protocol:	Ethernet, Fast Ethernet, Gigabit Ethernet, 10 Gigabit Ethernet
Remote Management Protocol:	IPMI 2.0
Features:	Intel Remote Management Module Support, integrated BMC with IPMI

Miscellaneous

Included Accessories:	2 x PCI-Express (1x16) Riser Card, 2 x CPU Heatsink, air duct, 4 x 3.5" hot-swap drive trays, standard control panel assembly, front I/O panel assembly, 6 x system fans, 8 x DIMM slot blanks, chassis stiffener bar, 2 x standard CPU carriers, power supply bay blank insert, 2 x CPU heatsink "NO CPU" labels insert, Chassis with Quick Reference Label affixed to top cover, Intel Server Board S2600WF0R
Cables Included:	I2C cable Mini SAS HD cable

Expansion / Connectivity

Bays:	4 (total) / 4 (free) x hot-swap 2.5" / 3.5" shared 2 (total) / 2 (free) x internal M.2
Slots:	2 (total) / 2 (free) x PCIe 3.0 x16
Interfaces:	5 x USB 3.0 (2 front, 3 rear) 1 x USB 2.0 - Type A (1 internal) 2 x LAN (10Gigabit Ethernet) - RJ-45 2 x serial 1 x management (Gigabit Ethernet) - RJ-45