

Intel Server System R1304WFTYSR - rack-mountable no CPU - 0 GB - no HDD



Not in stock

SKU	R1304WFTYSR
Product Description:	Intel Server System R1304WFTYSR - rack-mountable no CPU - 0 GB - no HDD
Type:	Server - rack-mountable
Height (Rack Units):	1U
Server Scalability:	2-way
Processor:	No CPU
Processor Socket:	Socket P
RAM:	0 GB DDR4 SDRAM - ECC

General

Type:	Server
Product Form Factor:	Rack-mountable - 1U
Embedded Security:	Trusted Platform Module (TPM 2.0) Security Chip
Server Scalability:	2-way
Internal Bays Qty:	2
Front Accessible Bays Qty:	4
Hot-Swap Bays Qty:	4

Processor / Chipset

CPU:	No CPU
Max CPU Qty:	2
CPU Upgradability:	Upgradable
CPU Socket:	Socket P
Chipset Type:	Intel C624

RAM

Installed Size:	0 GB
Technology:	DDR4 SDRAM - ECC

Dimensions & Weight

Width:	43 cm
Depth:	71 cm
Height:	4.37 cm

Manufacturer Warranty

Service & Support:	Limited warranty - 3 years
--------------------	----------------------------

Power

Device Type:	Power supply
Power Redundancy:	Optional
Power Redundancy Scheme:	1+1 (with optional power supply)
Installed Qty:	1
Power Provided:	1100 Watt

Miscellaneous

RAM

Form Factor: DIMM 288-pin

Slots: 24 (Total) / 24 (empty)

Features: Registered, Load-Reduced DIMM (LRDIMM)

Hard Drive

Type: No HDD

Storage Controller

Type: RAID

Controller Interface Type: SATA 6Gb/s

Channel Qty: 10

RAID Level: RAID 0, RAID 1, RAID 10

Optical Storage

Type: No optical drive

Monitor

Monitor Type: None.

Miscellaneous

Included: 2 x PCI-Express (1x16) Riser Card, 2 x CPU Heatsink, air duct, 4 x 3.5" hot-swap drive trays, 12Gb SAS backplane, 4 x 3.5" hot swap drive tool less carriers, standard control panel assembly, front I/O panel assembly, 6 x system fans, 2 x standard CPU carriers, 2 x CPU heatsink "NO CPU" labels insert, Chassis with Quick Reference Label affixed to top cover, Intel Server Board S2600WFTR

Accessories:

Cables Included: I2C cable ; Mini SAS HD cable (2 pcs.) ; Power cable

Expansion / Connectivity

Bays: 4 (total) / 4 (free) x hot-swap 2.5" / 3.5" shared ; 2 internal M.2

Slots: 2 (total) / 2 (free) x PCIe 3.0 x16

Interfaces: 5 x USB ; 2 x LAN (10Gigabit Ethernet) - RJ-45 ; 2 x serial ; Management

Networking

Ethernet Ports: 2 x 10 Gigabit Ethernet

Data Link Protocol: Ethernet, Fast Ethernet, Gigabit Ethernet, 10 Gigabit Ethernet

Remote Management Protocol: IPMI 2.0

Features: Integrated BMC with IPMI

