

Intel Server System R1304WFTZSR - rack-mountable - no CPU - 0 GB - no HDD



06-06-2024

SKU	R1304WFTZSR
Product Description:	Intel Server System R1304WFTZSR - rack-mountable - no CPU - 0 GB - no HDD
Type:	Server - rack-mountable
Height (Rack Units):	1U
Server Scalability:	2-way
Processor:	No CPU
Processor Socket:	Socket P
RAM:	0 GB DDR4 SDRAM - ECC

General

Type:	Server
Product Form Factor:	Rack-mountable - 1U
Embedded Security:	Trusted Platform Module (TPM 2.0) Security Chip
Server Scalability:	2-way
Internal Bays Qty:	2
Front Accessible Bays Qty:	4
Hot-Swap Bays Qty:	4

Processor / Chipset

CPU:	No CPU
Max CPU Qty:	2
CPU Upgradability:	Upgradable
CPU Socket:	Socket P
Chipset Type:	Intel C624

RAM

Installed Size:	0 GB
Technology:	DDR4 SDRAM - ECC

Dimensions & Weight

Dimensions & Weight Details:	57.7 cm - 98.3 cm - 26 cm
Width:	43.9 cm
Depth:	71.2 cm
Height:	4.32 cm

Manufacturer Warranty

Service & Support:	Limited warranty - 3 years
--------------------	----------------------------

Power

Device Type:	Power supply
Power Redundancy:	Optional
Power Redundancy Scheme:	1+1 (with optional power supply)
Installed Qty:	1
Power Provided:	1300 Watt

Miscellaneous

RAM

Form Factor:	DIMM 288-pin
Slots:	24 (Total) / 24 (empty)
Features:	Registered, Load-Reduced DIMM (LRDIMM)

Hard Drive

Type:	No HDD
-------	--------

Storage Controller

Type:	RAID
Controller Interface Type:	SATA 6Gb/s
Channel Qty:	10
RAID Level:	RAID 0, RAID 1, RAID 10

Optical Storage

Type:	No optical drive
-------	------------------

Monitor

Monitor Type:	None.
---------------	-------

Miscellaneous

Included Accessories:	2 x PCI-Express (1x16) Riser Card, 2 x CPU Heatsink, air duct, 4 x 3.5" hot-swap drive trays, standard control panel assembly, front I/O panel assembly, 6 x system fans, 8 x DIMM slot blanks, chassis stiffener bar, 2 x standard CPU carriers, power supply bay blank insert, 2 x CPU heatsink "NO CPU" labels insert, Chassis with Quick Reference Label affixed to top cover, Intel Server Board S2600WFTR, SATA optical drive power
-----------------------	---

Cables Included:	I2C cable Mini SAS HD cable Power cable Serial ATA cable
------------------	--

Expansion / Connectivity

Bays:	4 (total) / 4 (free) x hot-swap 2.5" / 3.5" shared 2 internal M.2
Slots:	2 (total) / 2 (free) x PCIe 3.0 x16
Interfaces:	5 x USB 2 x LAN (10Gigabit Ethernet) - RJ-45 2 x serial Management

Networking

Ethernet Ports:	2 x 10 Gigabit Ethernet
Data Link Protocol:	Ethernet, Fast Ethernet, Gigabit Ethernet, 10 Gigabit Ethernet
Remote Management Protocol:	IPMI 2.0
Features:	Integrated BMC with IPMI

