

Intel Server System R2208GZ4IS - rack-mountable - no CPU - 0 GB - no HDD



26-09-2024

SKU	R2208GZ4IS
Product Description:	Intel Server System R2208GZ4IS - rack-mountable - no CPU - 0 GB - no HDD
Type:	Server - rack-mountable
Height (Rack Units):	2U
Server Scalability:	2-way
Processor:	No CPU
Processor Socket:	LGA2011 Socket
RAM:	0 GB DDR3 SDRAM

General

Type:	Server
Product Form Factor:	Rack-mountable - 2U
Server Scalability:	2-way
Front Accessible Bays Qty:	1
Hot-Swap Bays Qty:	8

Processor / Chipset

CPU:	No CPU
Max CPU Qty:	2
CPU Upgradability:	Upgradable
CPU Socket:	LGA2011 Socket
Chipset Type:	Intel C600-A

RAM

Installed Size:	0 GB
Technology:	DDR3 SDRAM
Form Factor:	DIMM 240-pin
Slots:	24 (Total) / 24 (empty)

Environmental Parameters

Min Operating Temperature:	10 °C
Max Operating Temperature:	35 °C

Dimensions & Weight

Width:	43 cm
Depth:	71 cm
Height:	8.7 cm

Manufacturer Warranty

Service & Support:	Limited warranty - 3 years
--------------------	----------------------------

Power

Device Type:	Power supply
Power Redundancy:	Yes
Power Redundancy Scheme:	1+1
Installed Qty:	1
Max Supported Qty:	2
Voltage Required:	DC -48 V
Power Provided:	750 Watt

Miscellaneous

Produktdatablad genereret d. 16-09-2024 21:51.

Vær opmærksom på at priser og lagerstatus var gældende på genereringstidspunktet og dermed ikke kan garanteres.

RAM

Features: Unbuffered, registered, quad channel memory architecture, Load-Reduced DIMM (LRDIMM)

Hard Drive

Type: No HDD

Storage Controller

Type: 1 x SATA - integrated

Controller Interface Type: SATA 6Gb/s

Channel Qty: 2

Storage Controller (2nd)

Type: 1 x SAS - integrated

Controller Interface Type: SATA 3Gb/s / SAS

Channel Qty: 8

Optical Storage

Type: No optical drive

Monitor

Monitor Type: None.

Graphics Controller

Type: Integrated

Video Memory: 16 MB DDR3 SDRAM

Video Interfaces: VGA

Miscellaneous

Included Accessories: 2 x CPU Heatsink, air duct, 2 x riser cards, rack rail kit

Cables Included: Serial ATA / SAS cable (2 pcs.)

Expansion / Connectivity

Bays: 8 (total) / 8 (free) x hot-swap 2.5" ; 1 (total) / 1 (free) x external 5.25" Slim Line

Slots: 2 (total) / 2 (free) x CPU ; 24 (total) / 24 (free) x DIMM 240-pin ; 2 (total) / 2 (free) x PCIe 3.0 x16 ; 6 (total) / 6 (free) x PCIe 3.0 x8 ; 1 (total) / 1 (free) x expansion slot

Interfaces: 2 x VGA (1 front, 1 rear) ; 5 x USB 2.0 (2 front, 3 rear) ; 1 x serial ; 4 x LAN (Gigabit Ethernet) ; 1 x management

Networking

Type: Integrated

Ethernet Ports: 4 x Gigabit Ethernet

Data Link Protocol: Ethernet, Fast Ethernet, Gigabit Ethernet

Remote Management Protocol: IPMI 2.0