

Intel Server System R2208WFOZSR - rack-mountable no CPU - 0 GB - no HDD



Not in stock

SKU	R2208WFOZSR
Product Description:	Intel Server System R2208WFOZSR - rack-mountable no CPU - 0 GB - no HDD
Type:	Server - rack-mountable
Height (Rack Units):	2U
Server Scalability:	2-way
Processor:	No CPU
Processor Socket:	Socket P
RAM:	0 GB DDR4 SDRAM - ECC

General

Type:	Server
Product Form Factor:	Rack-mountable - 2U
Embedded Security:	Trusted Platform Module (TPM 2.0) Security Chip
Server Scalability:	2-way
Internal Bays Qty:	4
Front Accessible Bays Qty:	8
Hot-Swap Bays Qty:	8

Processor / Chipset

CPU:	No CPU
Max CPU Qty:	2
CPU Upgradability:	Upgradable
CPU Socket:	Socket P
Chipset Type:	Intel C624

RAM

Installed Size:	0 GB
Technology:	DDR4 SDRAM - ECC

Dimensions & Weight

Width:	43 cm
Depth:	71 cm
Height:	8.74 cm

Manufacturer Warranty

Service & Support:	Limited warranty - 3 years
--------------------	----------------------------

Power

Device Type:	Power supply
Power Redundancy:	Optional
Power Redundancy Scheme:	1+1 (with optional power supply)
Installed Qty:	1
Max Supported Qty:	2
Power Provided:	1300 Watt

Miscellaneous

RAM

Form Factor: DIMM 288-pin

Slots: 24 (Total) / 24 (empty)

Features: Registered, Load-Reduced DIMM (LRDIMM)

Hard Drive

Type: No HDD

Storage Controller

Type: RAID

Controller Interface Type: SATA 6Gb/s

Channel Qty: 10

RAID Level: RAID 0, RAID 1, RAID 10

Optical Storage

Type: No optical drive

Monitor

Monitor Type: None.

Networking

Data Link Protocol: Ethernet, Fast Ethernet, Gigabit Ethernet

Remote Management Protocol: IPMI 2.0

Features: Integrated BMC with IPMI

Miscellaneous

2 x CPU Heatsink, air duct, standard control panel assembly, front I/O panel assembly, 6 x system fans, 8 x DIMM slot blanks, 2 x riser card brackets, 2 x 3-slot PCIe riser cards, 2-slot low profile PCIe riser card, SAS/NVMe combo backplane, 8 x 2.5" hot swap drive tool less carriers, Chassis with Quick Reference Label affixed to top cover, Intel Server Board S2600WFOR, 2 x CPU heatsink "NO CPU" Mylar spacer insert

Cables Included: I2C cable ; Mini SAS HD cable (2 pcs.) ; Power cable

Expansion / Connectivity

Bays: 8 (total) / 8 (free) x hot-swap 2.5" ; 2 internal 2.5" / 2xM.2 shared

Slots: 1 (total) / 1 (free) x PCIe 3.0 x4 ; 3 (total) / 3 (free) x PCIe 3.0 x8 ; 2 (total) / 2 (free) x PCIe 3.0 x16

Interfaces: 5 x USB ; 1 x LAN ; 2 x serial

