

Intel Server System R2308WFTZS - rack-mountable - no CPU - 0 GB - no HDD



23-05-2024

SKU	R2308WFTZS
Product Description:	Intel Server System R2308WFTZS - rack-mountable - no CPU - 0 GB - no HDD
Type:	Server - rack-mountable
Height (Rack Units):	2U
Server Scalability:	2-way
Processor:	No CPU
Processor Socket:	Socket P
RAM:	0 GB DDR4 SDRAM - ECC

General

Type:	Server
Product Form Factor:	Rack-mountable - 2U
Embedded Security:	Trusted Platform Module (TPM 2.0) Security Chip
Server Scalability:	2-way
Internal Bays Qty:	4
Front Accessible Bays Qty:	8
Hot-Swap Bays Qty:	8

Processor / Chipset

CPU:	No CPU
Max CPU Qty:	2
CPU Upgradability:	Upgradable
CPU Socket:	Socket P
Chipset Type:	Intel C624

RAM

Installed Size:	0 GB
Technology:	DDR4 SDRAM - ECC

Dimensions & Weight

Width:	43 cm
Depth:	71 cm
Height:	8.74 cm

Manufacturer Warranty

Service & Support:	Limited warranty - 3 years
--------------------	----------------------------

Power

Device Type:	Power supply
Power Redundancy:	Optional
Installed Qty:	1
Power Provided:	1300 Watt

Miscellaneous

RAM

Form Factor:	DIMM 288-pin
Slots:	24 (Total) / 24 (empty)
Features:	Registered, Load-Reduced DIMM (LRDIMM)

Hard Drive

Type:	No HDD
-------	--------

Storage Controller

Type:	RAID
Controller Interface Type:	SATA 6Gb/s
Channel Qty:	12
RAID Level:	RAID 0, RAID 1, RAID 10

Optical Storage

Type:	No optical drive
-------	------------------

Monitor

Monitor Type:	None.
---------------	-------

Networking

Ethernet Ports:	2 x 10 Gigabit Ethernet
Data Link Protocol:	Ethernet, Fast Ethernet, Gigabit Ethernet, 10 Gigabit Ethernet
Remote Management Protocol:	IPMI 2.0
Features:	Integrated BMC with IPMI

Miscellaneous

Included Accessories:	2 x CPU Heatsink, air duct, 2 rack handles, 12Gb SAS backplane, standard control panel assembly, front I/O panel assembly, 6 x system fans, 8 x DIMM slot blanks, 2 x standard CPU carriers, power supply bay blank insert, Intel Server Board S2600WFT, 2 x CPU heatsink "NO CPU" labels insert, 2 x riser card brackets, 2 x 3-slot PCIe riser cards, 2-slot low profile PCIe riser card, 2 x power cord retention straps assembly, 3 x RMFBU mounting brackets, 3.5" hot swap drive bay, 3.5" hot swap drive tool less carriers
Cables Included:	I2C cable Mini SAS HD cable (2 pcs.) Power cable (2 pcs.)

Expansion / Connectivity

Bays:	8 (total) / 8 (free) x hot-swap 2.5" / 3.5" shared 2 internal 2.5" / 2xM.2 shared
Slots:	2 (total) / 2 (free) x CPU 24 (total) / 24 (free) x DIMM 288-pin 6 (total) / 6 (free) x PCIe 3.0 x8
Interfaces:	5 x USB 2 x LAN (10Gigabit Ethernet) 2 x serial