

Intel Server System R2312WFONPR - rack-mountable - no CPU - 0 GB - no HDD



Not in stock

SKU R2312WFONPR

Product Description: Intel Server System R2312WFONPR - rack-mountable - no CPU - 0 GB - no HDD

Type: Server - rack-mountable

Height (Rack Units): 2U

Server Scalability: 2-way

Processor: No CPU

Processor Socket: Socket P

RAM: 0 GB DDR4 SDRAM - ECC

General

Type: Server

Product Form Factor: Rack-mountable - 2U

Embedded Security: Trusted Platform Module (TPM 2.0) Security Chip

Server Scalability: 2-way

Internal Bays Qty: 4

Front Accessible Bays Qty: 12

Hot-Swap Bays Qty: 12

Processor / Chipset

CPU: No CPU

Max CPU Qty: 2

CPU Upgradability: Upgradable

CPU Socket: Socket P

Chipset Type: Intel C624

RAM

Installed Size: 0 GB

Technology: DDR4 SDRAM - ECC

Dimensions & Weight

Width: 43 cm

Depth: 71 cm

Height: 8.74 cm

Manufacturer Warranty

Service & Support: Limited warranty - 3 years

Power

Device Type: Power supply

Power Redundancy: Optional

Installed Qty: 1

Power Provided: 1300 Watt

Miscellaneous

RAM

Form Factor:	DIMM 288-pin
Slots:	24 (Total) / 24 (empty)
Features:	Registered, Load-Reduced DIMM (LRDIMM)

Hard Drive

Type:	No HDD
-------	--------

Storage Controller

Type:	RAID
Controller Interface Type:	SATA 6Gb/s
Channel Qty:	10
RAID Level:	RAID 0, RAID 1, RAID 10

Optical Storage

Type:	No optical drive
-------	------------------

Monitor

Monitor Type:	None.
---------------	-------

Networking

Data Link Protocol:	Ethernet, Fast Ethernet, Gigabit Ethernet
Remote Management Protocol:	IPMI 2.0

Miscellaneous

Included Accessories:	2 x CPU Heatsink, air duct, 2 rack handles, 6 x system fans, 2 x standard CPU carriers, power supply bay blank insert, 2 x riser card brackets, 2 x 3-slot PCIe riser cards, 2-slot low profile PCIe riser card, 2 x power cord retention straps assembly, SAS/NVMe combo backplane, 12 x 3.5" hot-swap drive tool less carriers, 16 x DIMM slot blanks, Chassis with Quick Reference Label affixed to top cover, Intel Server Board S2600WFOR, 2 x CPU heatsink "NO CPU" Mylar spacer insert, 12 x 3.5" hot-swap drive bays with drive carriers and blanks, storage rack handle assembly
-----------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Cables Included:	I2C cable Mini SAS HD cable (3 pcs.) Power cable
------------------	------------------------------------------------------

Expansion / Connectivity

Bays:	12 (total) / 12 (free) x hot-swap 2.5" / 3.5" shared 2 internal 2.5" / 2xM.2 shared
-------	---------------------------------------------------------------------------------------

Slots:	6 (total) / 6 (free) x PCIe 3.0 x8
--------	------------------------------------

Interfaces:	5 x USB 2 x serial
-------------	----------------------

