

Intel Server System SR1530HCLSR - rack-mountable - no CPU - 0 GB - no HDD



16-05-2024

SKU	SR1530HCLSR
Product Description:	Intel Server System SR1530HCLSR - rack-mountable - no CPU - 0 GB - no HDD
Type:	Server - rack-mountable
Height (Rack Units):	1U
Server Scalability:	2-way
Processor:	No CPU
Processor Socket:	LGA771 Socket
RAM:	0 GB (installed) / 12 GB (max) - DDR2 SDRAM - ECC

General

Type:	Server
Product Form Factor:	Rack-mountable - 1U
Server Scalability:	2-way
Front Accessible Bays Qty:	1
Hot-Swap Bays Qty:	3

Processor / Chipset

CPU:	No CPU
Max CPU Qty:	2
CPU Upgradability:	Upgradable
CPU Socket:	LGA771 Socket
Chipset Type:	Intel 5000V
Front Side Bus:	1333 MHz

RAM

Installed Size:	0 GB / 12 GB (max)
Technology:	DDR2 SDRAM - ECC
Form Factor:	FB-DIMM 240-pin
Slots:	6 (Total) / 6 (empty)

Environmental Parameters

Min Operating Temperature:	10 °C
Max Operating Temperature:	35 °C
Humidity Range Operating:	0 - 95%

Dimensions & Weight

Width:	43 cm
Depth:	50.8 cm
Height:	4.3 cm

Operating System / Software

OS Certified:	Microsoft Windows 2000 Advanced Server, SUSE Linux Enterprise Server, Microsoft Windows Server 2003 Enterprise Edition, Novell NetWare 6.5, Red Hat Enterprise Linux 4
---------------	--

Power

Device Type:	Power supply
Installed Qty:	1
Power Provided:	400 Watt
Power Factor Correction:	Yes

Miscellaneous

RAM

Features: Dual channel memory architecture, Memory Mirroring, Fully Buffered

Upgrade Rule:	2 modules at a time
---------------	---------------------

Hard Drive

Type: No HDD

Storage Controller

Type: 1 x SAS - integrated

Controller Interface Type:	SAS
----------------------------	-----

Channel Qty: 4

RAID Level:	RAID 0, RAID 1, RAID 10
-------------	-------------------------

Storage Controller (2nd)

Type: 1 x IDE - integrated

Controller Interface Type:	ATA-100
----------------------------	---------

Optical Storage

Type: No optical drive

Monitor

Monitor Type: None.

Graphics Controller

Type: Integrated

Graphics Processor:	ATI ES1000
---------------------	------------

Video Memory: 16 MB DDR SDRAM

Video Interfaces:	VGA
-------------------	-----

Miscellaneous

Cables Included: Serial ATA cable (2 pcs.) ; IDE cable

Expansion / Connectivity

Bays: 3 (total) / 3 (free) x hot-swap 3.5" ; 1 (total) / 1 (free) x external 5.25" Slim Line

Slots:	2 (total) / 2 (free) x CPU ; 6 (total) / 6 (free) x FB-DIMM 240-pin ; 1 (total) / 1 (free) x PCIe x8 - low-profile ; 1 (total) / 1 (free) x PCI-X / 133 MHz - full-height ; 1 (total) / 0 (free) x Intel Adaptive Slot
--------	--

Interfaces: 2 x LAN (Gigabit Ethernet) ; 1 x PS/2 keyboard ; 1 x PS/2 mouse ; 1 x VGA ; 2 x USB 2.0 ; 1 x serial

Networking

Type: Integrated

Ethernet Ports:	2 x Gigabit Ethernet
-----------------	----------------------

Data Link Protocol: Ethernet, Fast Ethernet, Gigabit Ethernet

Remote Management Protocol:	IPMI 2.0
-----------------------------	----------