

Intel Wi-Fi 6 AX200 - Desktop Kit - network adapter - M.2 2230



In Stock(68)

SKU	AX200.NGWG.DTK
Product Description:	Intel Wi-Fi 6 AX200 - Desktop Kit - network adapter - M.2 2230
Device Type:	Network adapter
Form Factor:	Plug-in card
Interface (Bus) Type:	M.2 2230
Dimensions (WxDxH):	3 cm x 0.24 cm x 2.2 cm
Weight:	2.83 g
Data Link Protocol:	Wi-Fi 5, 802.11ax, Bluetooth 5.1



General

Device Type:	Network adapter
Form Factor:	Plug-in card
Interface (Bus) Type:	M.2 2230

Networking

Connectivity Technology:	Wireless
--------------------------	----------

Data Link Protocol:	IEEE 802.11b, IEEE 802.11a, IEEE 802.11g, IEEE 802.11n, IEEE 802.11ac, 802.11ax, Bluetooth 5.1
---------------------	--

Frequency Band:	2.4 GHz, 5 GHz
-----------------	----------------

Features:	Under vPro, 2x2 MU-MIMO technology
-----------	------------------------------------

Compliant Standards:	IEEE 802.11b, IEEE 802.11a, IEEE 802.11d, IEEE 802.11g, IEEE 802.11i, IEEE 802.11h, IEEE 802.11e, IEEE 802.11n, IEEE 802.11k, IEEE 802.11ac, IEEE 802.11w, IEEE 802.11r, IEEE 802.11u, IEEE 802.11v, Bluetooth 5.0, IEEE 802.11ax, Wi-Fi CERTIFIED 6
----------------------	--

Environmental Parameters

Min Operating Temperature:	0 °C
----------------------------	------

Max Operating Temperature:	80 °C
----------------------------	-------

Humidity Range Operating:	50 - 90% (non-condensing)
---------------------------	---------------------------

Dimensions & Weight

Width:	3 cm
--------	------

Depth:	0.24 cm
--------	---------

Height:	2.2 cm
---------	--------

Weight:	2.83 g
---------	--------

Software / System Requirements

OS Required:	Linux, Google Chrome OS, Windows 10 64-bit Edition
--------------	--

Miscellaneous

Included Accessories:	Low-profile bracket, full-height bracket
-----------------------	--

Cables Included:	2 x coaxial RF cable
------------------	----------------------

Encryption Algorithm:	128-bit WEP, 64-bit WEP, TLS, PEAP, TTLS, TKIP, WPA, FIPS 140-2, WPA2, WPA2-Enterprise, 128-bit AES-CCMP, EAP-SIM, EAP-AKA, WPA3, 256-bit AES-GCMP
-----------------------	--

Compliant Standards:	UL, cUL, CB, IEC 60950-1
----------------------	--------------------------

Aerial

Antenna:	External detachable
----------	---------------------

Antenna Qty:	2
--------------	---

