

Lenovo ThinkSystem DB610S - switch - 8 ports - Managed - rack-mountable



In Stock(2)

SKU	6559F4A
Product Description:	Lenovo ThinkSystem DB610S - switch - 8 ports - Managed - rack-mountable
Device Type:	Switch - 8 ports - Managed
Enclosure Type:	Rack-mountable 1U
Subtype:	Fibre Channel
Ports:	8 x 32Gb Fibre Channel SFP+
Performance:	Aggregate throughput: 768 Gbps Switching latency: 0.9 µs
Capacity:	Maximum frame size: 2112 byte Frame buffers: 2000

General

Device Type:	Switch - 8 ports - Managed
Enclosure Type:	Desktop, rack-mountable 1U
Subtype:	Fibre Channel
Ports:	8 x 32Gb Fibre Channel SFP+
Performance:	Aggregate throughput: 768 Gbps Switching latency: 0.9 µs
Capacity:	Maximum frame size: 2112 byte Frame buffers: 2000
Fibre Channel:	FC-DA, FC-FS, FC-GS-4, FC-SB, FC-SB-2, FC-SB-3, FC-SW-3, FC-Tape, FC-VI, FC-SP, FCP-4, FC-BB-2, FCP, FCP-2, FC-BB-5, FC-BB-3, FC-FS-2, FC-GS-5, FC-SW-4, FCP-3, FC-LS, FC-MI-2, FC-PI-4, FC-FS-3, FC-GS-6, FC-PI-3, FC-SW-5, FC-BB-4, FC-IFR, FC-PI-5, FC-LS-2, FC-SP-2, FC-SB-4, FC-DA-2, FC-MI-3, FC-BB-6, FC-SB-5, FC-FS-4, FC-SW-6, FC-GS-7, FC-PI-6, FC-GS-8, FC-LS-3, FC-SB-6, FC-SW-7, MIB-FA
Remote Management Protocol:	SNMP 1, SNMP 2, SNMP 3, HTTP, HTTPS, SMI-5, SSH, SSH-2, CLI, SCP, SFTP
Encryption Algorithm:	SSL
Authentication Method:	RADIUS, TACACS+, LDAP, FCAP

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	40 °C
Humidity Range Operating:	10 - 85% (non-condensing)
Min Storage Temperature:	-25 °C
Max Storage Temperature:	70 °C
Humidity Range Storage:	10 - 90% (non-condensing)

Manufacturer Warranty

Service & Support:	Limited warranty - replacement - 1 year - response time: next business day Limited warranty - software application support - 3 years
--------------------	--

Dimensions & Weight

Width:	42.9 cm
Depth:	30.7 cm
Height:	4.3 cm
Weight:	4.2 kg

Miscellaneous

General

Features:

Syslog support, IPv6 support, IP address filtering, firmware upgradable, Full Fabric, event log, ACL support, QoS, enviromental monitoring, FEC, RSCN support, FSPF, FDMI, RBAC, DPS, DLS, RCS, SNS, FCAP, POST, NTP, flow mirroring, DFP, 3+1 redundant fans, TIZ, RRD

Miscellaneous

Included Accessories: 8 x 32 Gbps SW SFP+ transceivers

Cables Included: 1 x DB-9 to RJ-45 adapter

Rack Mounting Kit: Included

Compliant Standards: VCCI, EN 61000-3-2, ICES-003, EN 61000-3-3, EN55024, CISPR 22, FCC Part 15 B, UL 60950-1, IEC 60950-1, EN 60950-1, GB 9254, CNS 13438, KN32, KN35, CNS 14336-1, EN 55032

Power

Power Device: Internal power supply

Power Provided: 150 Watt

Voltage Required: AC 120/230 V (50/60 Hz)

Expansion / Connectivity

Interfaces: 8 x 4/8/16/32Gb Fibre Channel SFP+ | 1 x management (Gigabit LAN) RJ-45 | 1 x serial RJ-45 | 1 x USB | 16 x 4/8/16/32Gb Fibre Channel SFP+ Ports on Demand

