

Lenovo ThinkSystem DB610S - switch - 8 ports - Managed - rack-mountable - with 8 x 32 Gbps SWL SFP+ transceivers



27-06-2024

SKU	7D8PA002WW
Product Description:	Lenovo ThinkSystem DB610S - switch - 8 ports - Managed - rack-mountable - with 8 x 32 Gbps SWL SFP+ transceivers
Device Type:	Switch - 8 ports - Managed - with 8 x 32 Gbps SWL SFP+ transceivers
Enclosure Type:	Rack-mountable 1U
Subtype:	Fibre Channel
Ports:	8 x 32Gb Fibre Channel SFP+
Performance:	Aggregate throughput: 768 Gbps Switching latency: 0.9 µs
Capacity:	Maximum frame size: 2112 byte Frame buffers: 2000

General

Device Type:	Switch - 8 ports - Managed - with 8 x 32 Gbps SWL SFP+ transceivers
Enclosure Type:	Desktop, rack-mountable 1U
Subtype:	Fibre Channel
Ports:	8 x 32Gb Fibre Channel SFP+
Performance:	Aggregate throughput: 768 Gbps Switching latency: 0.9 µs
Capacity:	Maximum frame size: 2112 byte Frame buffers: 2000
Remote Management Protocol:	SNMP, SMI-S, SSH, CLI, SCP, SFTP, RADIUS
Encryption Algorithm:	SSL
Authentication Method:	RADIUS, TACACS+, LDAP, FCAP
Features:	LDAP support, Full Fabric, ACL support, Adaptive Networking, RBAC, Advanced Zoning, Fabric Services, 4 redundant fans

Expansion / Connectivity

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	40 °C
Humidity Range Operating:	10 - 85% (non-condensing)
Min Storage Temperature:	-25 °C
Max Storage Temperature:	70 °C
Humidity Range Storage:	10 - 90% (non-condensing)

Manufacturer Warranty

Service & Support:	Limited warranty - lifetime - response time: next business day New releases update - lifetime
--------------------	---

Dimensions & Weight

Width:	42.9 cm
Depth:	30.7 cm
Height:	4.3 cm
Weight:	4.2 kg

Expansion / Connectivity

Interfaces:	8 x 4/8/16/32Gb Fibre Channel SFP+ 1 x management (Gigabit LAN) RJ-45 1 x serial RJ-45 1 x USB 16 x 4/8/16/32Gb Fibre Channel SFP+ Ports on Demand

Miscellaneous

Cables Included:	1 x serial cable
Rack Mounting Kit:	Included
Compliant Standards:	VCCI, EN 61000-3-2, ICES-003, EN 61000-3-3, EN55024, CISPR 22, FCC Part 15 B, RoHS, UL 60950-1, IEC 60950-1, EN 60950-1, GB 9254, CNS 13438, KN32, KN35, CNS 14336-1, EN 55032

Power

Power Device:	Internal power supply
Power Provided:	150 Watt
Voltage Required:	AC 100-240 V (50/60 Hz)

