

Lexmark CS431dw - printer - colour - laser



In Stock(19)

SKU	40N9421
Product Description:	Lexmark CS431dw - printer - colour - laser
Printer Type:	Workgroup printer - laser - colour
Weight:	16.1 kg
Media Size Class:	A4/Legal
Max Media Size:	Legal (216 x 356 mm), A4 (210 x 297 mm)
Print Speed:	Up to 24.7 ppm - B/W (ISO/IEC 24734) - A4 (210 x 297 mm) ; Up to 24.7 ppm - colour (ISO/IEC 24734) - A4 (210 x 297 mm) ; Up to 13 ppm - B/W duplex (ISO/IEC 24734) - A4 (210 x 297 mm) ; Up to 13 ppm - colour duplex (ISO/IEC 24734) - A4 (210 x 297 mm) ; Up to 26 ppm - B/W (ISO/IEC 24734) - ANSI A (Letter) (216 x 279 mm) ; Up to 26 ppm - colour (ISO/IEC 24734) - ANSI A (Letter) (216 x 279 mm) ; Up to 13 ppm - B/W duplex (ISO/IEC 24734) - ANSI A (Letter) (216 x 279 mm) ; Up to 13 ppm - colour duplex (ISO/IEC 24734) - ANSI A (Letter) (216 x 279 mm)
Max Resolution (B&W):	600 x 600 dpi

General

Printer Type: Workgroup printer - laser - colour

Printer

Print Speed: Up to 24.7 ppm - B/W (ISO/IEC 24734) - A4 (210 x 297 mm) ; Up to 24.7 ppm - colour (ISO/IEC 24734) - A4 (210 x 297 mm) ; Up to 13 ppm - B/W duplex (ISO/IEC 24734) - A4 (210 x 297 mm) ; Up to 13 ppm - colour duplex (ISO/IEC 24734) - A4 (210 x 297 mm) ; Up to 26 ppm - B/W (ISO/IEC 24734) - ANSI A (Letter) (216 x 279 mm) ; Up to 26 ppm - colour (ISO/IEC 24734) - ANSI A (Letter) (216 x 279 mm) ; Up to 13 ppm - B/W duplex (ISO/IEC 24734) - ANSI A (Letter) (216 x 279 mm) ; Up to 13 ppm - colour duplex (ISO/IEC 24734) - ANSI A (Letter) (216 x 279 mm)

Built-in Devices: LCD touch screen

Dimensions & Weight (Shipping)

Width (Shipping):	33.2 cm
Depth (Shipping):	55.6 cm
Height (Shipping):	51.9 cm
Weight (Shipping):	19.1 kg

Dimensions & Weight

Width:	41.12 cm
Depth:	39.41 cm
Height:	24.37 cm
Weight:	16.1 kg

Environmental Parameters

Min Operating Temperature:	10 °C
Max Operating Temperature:	32 °C

Printer

Preview Screen Size:	2.8"
Connectivity Technology:	Wireless
Interface:	USB 2.0, Gigabit LAN, Wi-Fi(ac)
AirPrint Enabled:	Yes
Max Resolution (B&W):	600 x 600 dpi
Max Resolution (Colour):	600 x 600 dpi
Max Resolution Class (B&W):	600 x 600 dpi
Max Resolution Class (Colour):	600 x 600 dpi
Image Enhancement Technology:	4800 Color Quality
Automatic Duplexing:	Yes
PostScript Support:	Standard
Language Simulation:	PCL 5, PostScript 3, PCL 6, PCLm
Fonts Included:	2 x bitmapped PCL ; 91 x scalable PostScript ; 89 x scalable PCL
Barcodes:	OCR-A, OCR-B
Media Handling:	250-sheet input tray, 1-sheet manual tray

Processor

Processor:	1 GHz
------------	-------

RAM

RAM Installed (Max):	512 MB / 512 MB (max)
----------------------	-----------------------

Environmental Parameters

Humidity Range Operating:	8 - 80%
---------------------------	---------

Manufacturer Warranty

Service & Support:	Limited warranty - 1 year - on-site
--------------------	-------------------------------------

Environmental Standards

EPEAT Compliant:	EPEAT Silver
ENERGY STAR:	Yes

Software / System Requirements

OS Required:	SuSE Linux Enterprise Server 11, SuSE Linux Enterprise Server 10, Microsoft Windows 7 (32/64 bits), Windows 8 (32/64 bits), Windows 10, SuSE Linux Enterprise Server 12, Microsoft Windows Server 2016, Ubuntu 16.04, openSUSE 42.3, Linux Fedora 27, openSUSE 15, Debian Linux 9.4, Debian GNU/Linux 8.11, Ubuntu 18.04 LTS, Red Hat Enterprise Linux WS 7.5, Linux Fedora 28
--------------	--

Miscellaneous

Consumables Included:	1 x toner cartridge (black) - up to 1500 pages ISO/IEC 19798 ; 1 x toner cartridge (cyan) - up to 1500 pages ISO/IEC 19798 ; 1 x toner cartridge (magenta) - up to 1500 pages ISO/IEC 19798 ; 1 x toner cartridge (yellow) - up to 1500 pages ISO/IEC 19798
Compliant Standards:	FCC Class B certified, BSMI, ICES-003 Class B, CCC, UL 60950-1, KCC, IEC 60825-1, FDA, UL-AR, EN 60825-1, KC, CECP, CEL, EMC Class B, EFTA, IEC/EN 60950-1, CAN/CSA-C22.2 No. 60950-1, RAL-UZ 205

Expansion / Connectivity

Connections:	1 x USB 2.0 - 4 pin USB Type B ; 1 x Gigabit LAN - RJ-45
--------------	--

Networking

Networking:	Print server
-------------	--------------

Networking

Remote Management Protocol:	SNMP 1, SNMP 3, SNMP 2c, HTTP, HTTPS, TFTP, IPP 1.0, IPP 1.1, IPP 2.0, NTP, ICMP, DHCP, IPv4, IPv6
-----------------------------	--

Security Protocols & Features:	SSL, TLS, IPsec, ARP, SNMP 3
--------------------------------	------------------------------

Duty Cycle

Monthly Duty Cycle (max):	75000 pages
---------------------------	-------------

Recommended Monthly Volume:	750 - 5000 pages
-----------------------------	------------------

Media Handling

Media Type:	Envelopes, labels, plain paper, card stock, glossy paper
-------------	--

Media Size Class:	A4/Legal
-------------------	----------

Max Media Size:	Legal (216 x 356 mm), A4 (210 x 297 mm)
-----------------	---

Media Sizes:	ANSI A (Letter) (216 x 279 mm), Legal (216 x 356 mm), Executive (184 x 267 mm), A4 (210 x 297 mm), A5 (148 x 210 mm), A6 (105 x 148 mm), Folio (216 x 330 mm), JIS B5 (182 x 257 mm), Statement (139.7 x 215.9 mm), Oficio (216 x 343 mm)
--------------	---

Envelope Sizes:	US No 10 (104.7 x 241.3 mm), International DL (110 x 220 mm), International C5 (162 x 229 mm), International B5 (176 x 250 mm), Monarch (98.4 x 190.5 mm), US No 9 (98.6 x 225.6 mm)
-----------------	--

Total Media Capacity:	250 sheets
-----------------------	------------

Media Feeders:	Bypass tray: 1 - 1 sheet ; Input tray: 1 - 250 sheets - (16 lbs (min) - 47 lbs (max)) ; Output tray: 1 - 100 sheets
----------------	---

Max Media Capacity:	750 sheets
---------------------	------------

Output Trays Capacity:	100 sheets
------------------------	------------