

Lexmark CS622de - printer - colour - laser



Not in stock

SKU	42C0091
Product Description:	Lexmark CS622de - printer - colour - laser
Printer Type:	Workgroup printer - laser - colour
Weight:	21 kg
Media Size Class:	A4/Legal
Max Media Size:	Legal (216 x 356 mm), A4 (210 x 297 mm)
Print Speed:	Up to 37 ppm - B/W - A4 (210 x 297 mm) ; Up to 37 ppm - colour - A4 (210 x 297 mm) ; Up to 19 spm - B/W duplex - A4 (210 x 297 mm) ; Up to 19 spm - colour duplex - A4 (210 x 297 mm)
Max Resolution (B&W):	1200 x 1200 dpi

General

Printer Type: Workgroup printer - laser - colour

Printer

Print Speed: Up to 37 ppm - B/W - A4 (210 x 297 mm) ; Up to 37 ppm - colour - A4 (210 x 297 mm) ; Up to 19 spm - B/W duplex - A4 (210 x 297 mm) ; Up to 19 spm - colour duplex - A4 (210 x 297 mm)

Built-in Devices:	Touch screen
Preview Screen Size:	4.3"
Connectivity Technology:	Wired
Interface:	USB 2.0, Gigabit LAN, USB 2.0 host
AirPrint Enabled:	Yes
Max Resolution (B&W):	1200 x 1200 dpi
Max Resolution (Colour):	1200 x 1200 dpi

Dimensions & Weight (Shipping)

Width (Shipping):	49.5 cm
Depth (Shipping):	59.5 cm
Height (Shipping):	40.2 cm
Weight (Shipping):	23.9 kg

Dimensions & Weight

Width:	44.2 cm
Depth:	42.1 cm
Height:	30.8 cm
Weight:	21 kg

Environmental Parameters

Min Operating Temperature:	10 °C
Max Operating Temperature:	32 °C
Humidity Range Operating:	8 - 80%
Sound Emission (Operating):	51 dBA

Manufacturer Warranty

Printer

Max Resolution Class (B&W): 1200 x 1200 dpi

Max Resolution Class (Colour): 1200 x 1200 dpi

Image Enhancement Technology: 4800 Color Quality

Automatic Duplexing: Yes

PostScript Support: Standard

First Print Out Time B/W: 9 sec

First Print Out Time Colour: 7 sec

Language Simulation: PCL 5C, PostScript 3, PCL 6, XPS, PDF 1.7

Fonts Included: 158 x scalable PostScript | 2 x bitmapped PCL | 39 x scalable PPDS | 5 x bitmapped PPDS | 84 x scalable PCL

Barcodes: OCR-A, OCR-B

Colour Management Features: Mopria

Media Handling: 250-sheet input tray, 1-sheet manual tray

Processor

Processor: 1000 MHz

RAM

RAM Installed (Max): 1 GB / 1 GB (max)

Media Handling

Media Type: Envelopes, labels, plain paper, card stock

Manufacturer Warranty

Service & Support: Limited warranty - 1 year - on-site - response time: next business day

Environmental Standards

Blue Angel: Yes

ENERGY STAR: Yes

Software / System Requirements

Software Included: Drivers & Utilities

OS Required: Novell NetWare 6.5, Novell NetWare 5.1 SP6 or later, Novell NetWare 6.0 SP3 or later, SunSoft Solaris x86 10, SuSE Linux Enterprise Server 11, Apple MacOS X 10.6, SuSE Linux Enterprise Server 10, IBM AIX 6.1, Microsoft Windows 7 (32/64 bits), SunSoft Solaris SPARC Platform Edition 10, Apple MacOS X Lion 10.7, IBM AIX 7.1, SunSoft Solaris x86 11, Red Hat Enterprise Linux WS 6, Apple OS X 10.8 Mountain Lion, Windows 8 (32/64 bits), SunSoft Solaris SPARC Platform Edition 11, Debian GNU/Linux 7.0, Windows 8.1 (32/64 bits), Apple OS X 10.9 Mavericks, Apple MacOS X 10.10, openSUSE 13.1, Windows 10, SuSE Linux Enterprise Server 12, openSUSE 13.2, Apple MacOS X 10.11, Debian GNU/Linux 8.0, Red Hat Enterprise Linux WS 7, Ubuntu 16.04 LTS, Apple macOS 10.12, Linux Fedora 23, Linux Fedora 24, openSUSE 42.3

Power

Power Device: Power supply - internal

Power Consumption Operational: 570 Watt

Power Consumption Stand by: 37 Watt

Power Consumption Sleep: 1.5 Watt

Miscellaneous

Media Handling

Media Size Class: A4/Legal

Max Media Size: Legal (216 x 356 mm), A4 (210 x 297 mm)

Media Sizes: ANSI A (Letter) (216 x 279 mm), Legal (216 x 356 mm), Executive (184 x 267 mm), A4 (210 x 297 mm), A5 (148 x 210 mm), A6 (105 x 148 mm), Folio (216 x 330 mm), JIS B5 (182 x 257 mm), Statement (139.7 x 215.9 mm), Oficio (216 x 343 mm)

Envelope Sizes: US No 10 (104.7 x 241.3 mm), International DL (110 x 220 mm), International C5 (162 x 229 mm), Monarch (98.4 x 190.5 mm), US No 9 (98.6 x 225.6 mm)

Total Media Capacity: 250 sheets

Media Feeders: Bypass tray: 1 x manual - 1 sheet | Input tray: 1 x automatic - 250 sheets weight: 90.3 g/m² - 105 g/m² | Output tray: 1 - 125 sheets

Max Media Capacity: 1450 sheets

Output Trays Capacity: 125 sheets

Miscellaneous

Consumables Included: 1 x toner cartridge (black) - up to 6000 pages ISO/IEC 19798 | 1 x toner cartridge (cyan) - up to 4000 pages ISO/IEC 19798 | 1 x toner cartridge (magenta) - up to 4000 pages ISO/IEC 19798 | 1 x toner cartridge (yellow) - up to 4000 pages ISO/IEC 19798 | 4 x photoconductor unit

Compliant Standards: FCC Class B certified, UL, C-Tick, cUL, GS, CB, ICES-003 Class B, CCC, DOC, UL 60950-1, IEC 60950-1, EN 60950-1, BSMI Class B, KCC, IEC 60825-1, FDA, UL-AR, EN 60825-1, KC, CECP, CEL, VCCI Class B, EFTA, CAN/CSA-C22.2 No. 60950-1

Expansion / Connectivity

Connections: 1 x USB 2.0 - 4 pin USB Type B | 1 x Gigabit LAN - RJ-45 | 2 x USB 2.0 host - 4 pin USB Type A

Networking

Networking: Print server

Remote Management Protocol: SNMP 1, Telnet, SNMP 3, SNMP 2c, HTTP, HTTPS, TFTP, IPP 1.0, IPP 1.1, IPP 2.0

Security Protocols & Features: SSL, TLS, ARP

Duty Cycle

Monthly Duty Cycle (max): 100000 pages

Recommended Monthly Volume: 1500 - 10000 pages

