

Lexmark CS720de - printer - colour - laser



Not in stock

SKU	40C9100
Product Description:	Lexmark CS720de - printer - colour - laser
Printer Type:	Workgroup printer - laser - colour
Weight:	36.3 kg
Media Size Class:	A4/Legal
Max Media Size:	Legal (216 x 356 mm), A4 (210 x 297 mm)
Print Speed:	Up to 40 ppm - B/W (ISO/IEC 24734) - ANSI A (Letter) (216 x 279 mm) ; Up to 40 ppm - colour (ISO/IEC 24734) - ANSI A (Letter) (216 x 279 mm) ; Up to 32 spm - B/W duplex (ISO/IEC 24734) - ANSI A (Letter) (216 x 279 mm)
Max Resolution (B&W):	1200 x 1200 dpi

General

Printer Type: Workgroup printer - laser - colour

Printer

Print Speed: Up to 40 ppm - B/W (ISO/IEC 24734) - ANSI A (Letter) (216 x 279 mm) ; Up to 40 ppm - colour (ISO/IEC 24734) - ANSI A (Letter) (216 x 279 mm) ; Up to 32 spm - B/W duplex (ISO/IEC 24734) - ANSI A (Letter) (216 x 279 mm)

Built-in Devices: Touch screen

Preview Screen Size: 4.3"

Connectivity Technology: Wired

Interface: USB 2.0, Gigabit LAN, USB 2.0 host

AirPrint Enabled: Yes

Max Resolution (B&W): 1200 x 1200 dpi

Dimensions & Weight (Shipping)

Width (Shipping):	64.3 cm
Depth (Shipping):	73.9 cm
Height (Shipping):	56.9 cm
Weight (Shipping):	41.9 kg

Dimensions & Weight

Width:	47.5 cm
Depth:	49.9 cm
Height:	41.7 cm
Weight:	36.3 kg

Environmental Parameters

Min Operating Temperature:	10 °C
Max Operating Temperature:	32 °C
Humidity Range Operating:	15 - 80% (non-condensing)
Sound Emission (Idle):	15 dBA

Printer

Max Resolution (Colour):	1200 x 1200 dpi
--------------------------	-----------------

Image Enhancement Technology:	4800 Color Quality
-------------------------------	--------------------

Automatic Duplexing:	Yes
----------------------	-----

PostScript Support:	Standard
---------------------	----------

First Print Out Time B/W:	6 sec
---------------------------	-------

First Print Out Time Colour:	6.5 sec
------------------------------	---------

Language Simulation:	PCL 5C, PostScript 3, PCL 6, XPS, PDF 1.7
----------------------	---

Fonts Included:	165 x scalable PostScript 2 x bitmapped PCL 39 x scalable PPDS 15 x bitmapped PPDS 84 x scalable PCL
-----------------	--

Barcodes:	OCR-A, OCR-B
-----------	--------------

Printer Features:	Internal card slot
-------------------	--------------------

Media Handling:	100-sheet multipurpose tray, 550-sheet input tray
-----------------	---

Processor

Processor:	1.2 GHz
------------	---------

RAM

RAM Installed (Max):	1 GB / 3 GB (max)
----------------------	-------------------

Media Handling

Media Type:	Envelopes, labels, plain paper, banner paper, card stock
-------------	--

Media Size Class:	A4/Legal
-------------------	----------

Max Media Size:	Legal (216 x 356 mm), A4 (210 x 297 mm)
-----------------	---

Environmental Parameters

Sound Emission (Operating):	51 dBA
-----------------------------	--------

Manufacturer Warranty

Service & Support:	Limited warranty - 1 year - on-site - response time: next business day
--------------------	--

Environmental Standards

ENERGY STAR:	Yes
--------------	-----

Software / System Requirements

OS Required:	SunSoft Solaris x86 10, Red Hat Enterprise Linux WS 4, SuSE Linux Enterprise Server 11, Microsoft Windows Server 2008 R2, Apple MacOS X 10.6, SUSE Linux Enterprise Desktop 11, SUSE Linux Enterprise Server 10, Red Hat Enterprise Linux WS 5, Novell Open Enterprise Server 2.0, IBM AIX 6.1, Microsoft Windows Vista (32/64 bits), Microsoft Windows 7 (32/64 bits), Microsoft Windows XP (32/64 bits), Microsoft Windows Server 2008 (32/64-bits), Apple MacOS X Lion 10.7, IBM AIX 7.1, SunSoft Solaris x86 11, Red Hat Enterprise Linux WS 6, Microsoft Windows Server 2012, Apple OS X 10.8 Mountain Lion, Windows 8 (32/64 bits), Debian GNU/Linux 7.0, Windows 8.1 (32/64 bits), Windows 8.1 RT, Microsoft Windows Server 2012 R2, Windows RT, Apple OS X 10.9 Mavericks, Novell Open Enterprise Server 11, Ubuntu 12.04 LTS, Ubuntu 15.04, Apple MacOS X 10.10, Ubuntu 14.04 LTS, openSUSE 13.1, Windows 10, SuSE Linux Enterprise Server 12, Red Hat Fedora 21, openSUSE 13.2, SUSE Linux Enterprise Desktop 12, Apple MacOS X 10.11, Debian GNU/Linux 8.0, Red Hat Fedora 22, Linux Linpus Lite Desktop 2.1, Linux Mint Debian 2, PCLinuxOS 2014.12, Red Hat Enterprise Linux WS 7, openSUSE Tumbleweed, Linux Mint 13 LTS, Linux Mint 17 LTS, Linux Mint 17.1 LTS, Linux Mint 17.2 LTS
--------------	---

Power

Power Consumption Operational:	560 Watt
--------------------------------	----------

Power Consumption Stand by:	80 Watt
-----------------------------	---------

Media Handling

Media Sizes:	ANSI A (Letter) (216 x 279 mm), Legal (216 x 356 mm), Executive (184 x 267 mm), A4 (210 x 297 mm), A5 (148 x 210 mm), A6 (105 x 148 mm), Folio (216 x 330 mm), JIS B5 (182 x 257 mm), Statement (139.7 x 215.9 mm), Oficio (216 x 343 mm)
Envelope Sizes:	US No 10 (104.7 x 241.3 mm), International DL (110 x 220 mm), International C5 (162 x 229 mm), International B5 (176 x 250 mm), Monarch (98.4 x 190.5 mm), US No 9 (98.6 x 225.6 mm)
Total Media Capacity:	650 sheets
Media Feeders:	Multi-purpose tray: 1 - 100 sheets - (16 lbs (min) - 58 lbs (max)) ; Input tray: 1 - 550 sheets - (16 lbs (min) - 58 lbs (max))
Max Media Capacity:	2300 sheets
Output Trays Capacity:	300 sheets

Duty Cycle

Monthly Duty Cycle (max):	120000 pages
Recommended Monthly Volume:	1500 - 15000 pages

Networking

Networking:	Print server
Remote Management Protocol:	SNMP 1, Telnet, SNMP 3, SNMP 2c, HTTP, HTTPS, TFTP, IPP 1.0, IPP 1.1, IPP 2.0
Security Protocols & Features:	SSL, Apple Bonjour, LEAP, TLS, IPsec, 802.1x, ARP, TTLS, PEAP, MD5, MS-CHAPv2

Power

Power Consumption Sleep:	2.4 Watt
--------------------------	----------

Miscellaneous

Consumables Included:	1 x toner cartridge (black) - up to 3000 pages ISO/IEC 19798 ; 1 x toner cartridge (cyan) - up to 3000 pages ISO/IEC 19798 ; 1 x toner cartridge (magenta) - up to 3000 pages ISO/IEC 19798 ; 1 x toner cartridge (yellow) - up to 3000 pages ISO/IEC 19798 ; 1 x imaging unit - up to 150000 pages at 5% coverage
Compliant Standards:	UL, C-Tick, cUL, GS, NOM, SABS, ICES-003 Class B, CCC, DOC, SII, BSMI Class B, Green Mark, IEC 60825-1, FDA, UL-AR, CDRH, KC, CECP, CEL, Green Dot, VCCI Class B, Directive 1275/2008/EC, ECMA-370, EFTA, TER, CoC, ISO 9296, NOM-032, ISO 532B, TED, CCD 035 EcoLogo

Expansion / Connectivity

Connections:	1 x USB 2.0 - 4 pin USB Type B ; 1 x Gigabit LAN ; 2 x USB 2.0 host - 4 pin USB Type A
--------------	--