

Lexmark CS725de - printer - colour - laser



16-05-2024

SKU	40C9040
Product Description:	Lexmark CS725de - printer - colour - laser
Printer Type:	Workgroup printer - laser - colour
Weight:	36.3 kg
Media Size Class:	A4/Legal
Max Media Size:	Legal (216 x 356 mm), A4 (210 x 297 mm)
Print Speed:	Up to 47 ppm - B/W - A4 (210 x 297 mm) ; Up to 47 ppm - colour - A4 (210 x 297 mm) ; Up to 38 ppm - B/W duplex - A4 (210 x 297 mm)
Max Resolution (B&W):	1200 x 1200 dpi

General

Printer Type: Workgroup printer - laser - colour

Printer

Print Speed: Up to 47 ppm - B/W - A4 (210 x 297 mm) ; Up to 47 ppm - colour - A4 (210 x 297 mm) ; Up to 38 ppm - B/W duplex - A4 (210 x 297 mm)

Built-in Devices:	Touch screen
Preview Screen Size:	4.3"
Connectivity Technology:	Wired
Interface:	USB 2.0, Gigabit LAN, USB 2.0 host
AirPrint Enabled:	Yes
Max Resolution (B&W):	1200 x 1200 dpi
Max Resolution (Colour):	1200 x 1200 dpi

Dimensions & Weight (Shipping)

Width (Shipping):	64.3 cm
Depth (Shipping):	73.8 cm
Height (Shipping):	56.8 cm
Weight (Shipping):	41.9 kg

Dimensions & Weight

Width:	47.5 cm
Depth:	49.9 cm
Height:	41.7 cm
Weight:	36.3 kg

Environmental Parameters

Min Operating Temperature:	10 °C
Max Operating Temperature:	32 °C
Humidity Range Operating:	15 - 80% (non-condensing)
Sound Emission (Idle):	15 dBA
Sound Emission (Operating):	51 dBA

Printer

Image Enhancement Technology: 4800 Color Quality

Automatic Duplexing: Yes

PostScript Support: Standard

First Print Out Time B/W: 5 sec

First Print Out Time Colour: 5.5 sec

Language Simulation: PCL 5C, PostScript 3, PCL 6, Adobe PPDS, XPS, PDF 1.7

Fonts Included: 165 x scalable PostScript | 2 x bitmapped PCL | 39 x scalable PPDS | 15 x bitmapped PPDS | 84 x scalable PCL

Barcodes: OCR-A, OCR-B

Media Handling: 100-sheet multipurpose tray, 550-sheet input tray

Processor

Processor: 1.2 GHz

RAM

RAM Installed (Max): 1 GB / 3 GB (max)

Media Handling

Media Type: Envelopes, transparencies, labels, plain paper, vinyl labels, card stock

Media Size Class: A4/Legal

Max Media Size: Legal (216 x 356 mm), A4 (210 x 297 mm)

Media Sizes: ANSI A (Letter) (216 x 279 mm), Legal (216 x 356 mm), Executive (184 x 267 mm), A4 (210 x 297 mm), A5 (148 x 210 mm), Folio (216 x 330 mm), JIS B5 (182 x 257 mm), Oficio (216 x 343 mm)

Manufacturer Warranty

Service & Support: Limited warranty - 1 year - on-site

Environmental Standards

ENERGY STAR: Yes

Software / System Requirements

Software Included: Drivers & Utilities

Microsoft Windows XP, Microsoft Windows XP 64-bit Edition, HP-UX 11.11, Microsoft Windows Server 2003, Novell NetWare 6.5, Novell NetWare 5.1 SP6 or later, Novell NetWare 6.0 SP3 or later, HP-UX 11.23, Microsoft Windows 7, IBM AIX 5.3, SunSoft Solaris x86 10, Red Hat Enterprise Linux WS 4, Microsoft Windows Vista, SuSE Linux Enterprise Server 11, Microsoft Windows Server 2008 R2, Apple MacOS X 10.6, SUSE Linux Enterprise Desktop 11, Microsoft Windows 7 64-bit Edition, Debian GNU/Linux 5.0, SUSE Linux Enterprise Desktop 10, SuSE Linux Enterprise Server 10, Microsoft Windows Server 2003 x64 Edition, Microsoft Windows Vista (64-bit versions), Red Hat Enterprise Linux WS 5, Microsoft Windows Server 2008, Apple MacOS X 10.5, IBM AIX 6.1, Microsoft Windows Server 2008 x64 Edition, HP-UX 11.31, Red Flag Linux Desktop 6.0, openSUSE 11.3, Linux Linpus Desktop 9.6, SunSoft Solaris SPARC Platform Edition 9, SunSoft Solaris SPARC Platform Edition 10, Red Hat Fedora 14, Apple MacOS X Lion 10.7, Red Hat Fedora 15, openSUSE 11.4, Windows 8, IBM AIX 7.1, Red Hat Fedora 16, Ubuntu 11.04, Linux Mint 11, SunSoft Solaris x86 11, Ubuntu 11.10, Debian GNU/Linux 6.0, Linux Mint 9, Linux Mint 10, Red Hat Enterprise Linux WS 6, Ubuntu 12.04, Microsoft Windows Server 2012, Apple OS X 10.8 Mountain Lion, openSUSE 12.2, Windows 8 64-bit Edition, openSUSE 12.1, Linux Mint 12, SunSoft Solaris SPARC Platform Edition 11, Red Hat Fedora 17, Ubuntu 12.10, Windows 8.1 64-bit Edition, Windows 8.1 RT, Microsoft Windows Server 2012 R2, Windows 8.1, Windows RT, Apple OS X 10.9 Mavericks, Linux Mint 13, PCLinuxOS 2011, Apple MacOS X 10.10

Power

Media Handling

Envelope Sizes: US No 10 (104.7 x 241.3 mm), International DL (110 x 220 mm), International C5 (162 x 229 mm), International B5 (176 x 250 mm), Monarch (98.4 x 190.5 mm), US No 9 (98.6 x 225.6 mm)

Media Weight: 60 g/m² - 218 g/m²

Total Media Capacity: 650 sheets

Media Feeders: 1 x automatic - 100 sheets | 1 x automatic - 550 sheets

Max Media Capacity: 2300 sheets

Output Trays Capacity: 300 sheets

Duty Cycle

Monthly Duty Cycle (max): 150000 pages

Recommended Monthly Volume: 2000 - 20000 pages

Networking

Networking: Print server

Remote Management Protocol: SNMP 1, Telnet, SNMP 3, SNMP 2c, HTTP, HTTPS, TFTP, IPP 1.0, IPP 1.1, IPP 2.0

Security Protocols & Features: SSL, Apple Bonjour, LEAP, TLS, IPsec, 802.1x, ARP

Expansion / Connectivity

Connections: 1 x USB 2.0 - 4 pin USB Type B | 1 x Gigabit LAN | 2 x USB 2.0 host - 4 pin USB Type A

Power

Power Device: Power supply

Power Consumption Operational: 570 Watt

Power Consumption Stand by: 80 Watt

Power Consumption Sleep: 2.4 Watt

Miscellaneous

Consumables Included: 1 x toner cartridge (black) - up to 7000 pages ISO/IEC 19798 | 1 x toner cartridge (cyan) - up to 7000 pages ISO/IEC 19798 | 1 x toner cartridge (magenta) - up to 7000 pages ISO/IEC 19798 | 1 x toner cartridge (yellow) - up to 7000 pages ISO/IEC 19798 | 1 x imaging unit - up to 150000 pages

Compliant Standards: C-Tick, EN55022, GS, EN55024, ICES-003 Class B, CCC, UL 60950-1, IEC 60950-1, EN 60950-1, BSMI Class B, KCC, IEC 60825-1, FDA, UL-AR, EN 60825-1, EN 62301, KC, CECP, CEL, EN 62311, VCCI Class B, EN 61000-3, EFTA