

Lexmark CS923DE - printer - colour - laser



06-06-2024

SKU	32C0013
Product Description:	Lexmark CS923DE - printer - colour - laser
Printer Type:	Workgroup printer - laser - colour
Weight:	88.5 kg
Max Media Size:	Tabloid Extra (305 x 457 mm), SRA3 (320 x 450 mm)
Print Speed:	Up to 55 ppm - B/W - A4 (210 x 297 mm) ; Up to 55 ppm - colour - A4 (210 x 297 mm) ; Up to 55 spm - B/W duplex - A4 (210 x 297 mm)
Max Resolution (B&W):	1200 x 1200 dpi
Max Resolution (Colour):	1200 x 1200 dpi

General

Printer Type: Workgroup printer - laser - colour

Printer

Print Speed: Up to 55 ppm - B/W - A4 (210 x 297 mm) ; Up to 55 ppm - colour - A4 (210 x 297 mm) ; Up to 55 spm - B/W duplex - A4 (210 x 297 mm)

Built-in Devices: Touch screen

Preview Screen Size: 4.3"

Connectivity Technology: Wired

Interface: USB 2.0, Gigabit LAN, USB 2.0 host

AirPrint Enabled: Yes

Max Resolution (B&W): 1200 x 1200 dpi

Max Resolution (Colour): 1200 x 1200 dpi

Dimensions & Weight (Shipping)

Width (Shipping): 75.8 cm

Depth (Shipping): 91.1 cm

Height (Shipping): 105.7 cm

Weight (Shipping): 103 kg

Dimensions & Weight

Width: 61.5 cm

Depth: 69.3 cm

Height: 78 cm

Weight: 88.5 kg

Environmental Parameters

Min Operating Temperature: 10 °C

Max Operating Temperature: 40 °C

Humidity Range Operating: 15 - 85%

Sound Emission (Idle): 26 dBA

Sound Emission (Operating): 54 dBA

Sound Emission (Quiet Mode): 50 dBA

Printer

Max Resolution Class (B&W): 1200 x 1200 dpi

Max Resolution Class (Colour): 1200 x 1200 dpi

Image Enhancement Technology: 2400 IQ

Automatic Duplexing: Yes

PostScript Support: Standard

First Print Out Time B/W: 5.1 sec

First Print Out Time Colour: 5.1 sec

Language Simulation: PCL 5C, PostScript 3, PCL 6, XPS, PDF 1.7

Fonts Included: 39 x scalable PPDS | 84 x scalable PCL | 165 x scalable PostScript | 15 x bitmapped PPDS | 2 x bitmapped PCL

Barcodes: OCR-A, OCR-B

Media Handling: 2x 500-sheet input trays, 150-sheet multipurpose tray

Processor

Processor: 1.2 GHz

RAM

RAM Installed (Max): 1 GB / 3 GB (max)

Media Handling

Media Type: Envelopes, labels, plain paper, banner paper, card stock

Max Media Size: Tabloid Extra (305 x 457 mm), SRA3 (320 x 450 mm)

Manufacturer Warranty

Service & Support: Limited warranty - 1 year - on-site - response time: next business day

Environmental Standards

Blue Angel: Yes

ENERGY STAR: Yes

Software / System Requirements

Software Included: Drivers & Utilities

Novell NetWare 6.5, IBM AIX 5.3, SunSoft Solaris x86 10, Red Hat Enterprise Linux WS 4, Novell Open Enterprise Server, SuSE Linux Enterprise Server 11, Microsoft Windows Server 2008 R2, Apple MacOS X 10.6, SUSE Linux Enterprise Desktop 11, SUSE Linux Enterprise Desktop 10, SuSE Linux Enterprise Server 10, Red Hat Enterprise Linux WS 5, IBM AIX 6.1, Microsoft Windows Vista (32/64 bits), Microsoft Windows 7 (32/64 bits), Microsoft Windows XP (32/64 bits), Microsoft Windows Server 2008 (32/64-bits), SunSoft Solaris SPARC Platform Edition 10, Apple MacOS X Lion 10.7, IBM AIX 7.1, SunSoft Solaris x86 11, Red Hat Enterprise Linux WS 6, Microsoft Windows Server 2012, Apple OS X 10.8 Mountain Lion, Windows 8 (32/64 bits), SunSoft Solaris SPARC Platform Edition 11, Debian GNU/Linux 7.0, Windows 8.1 (32/64 bits), Windows 8.1 RT, Microsoft Windows Server 2012 R2, Windows RT, Apple OS X 10.9 Mavericks, Ubuntu 12.04 LTS, Ubuntu 15.04, Apple MacOS X 10.10, Ubuntu 14.04 LTS, openSUSE 13.1, Windows 10, SuSE Linux Enterprise Server 12, Red Hat Fedora 21, openSUSE 13.2, SUSE Linux Enterprise Desktop 12, Apple MacOS X 10.11, Debian GNU/Linux 8.0, Red Hat Fedora 22, Linux Linpus Lite Desktop 2.1, Linux Mint Debian 2, PCLinuxOS 2014.12, Red Hat Enterprise Linux WS 7, openSUSE Tumbleweed, Apple macOS 10.12, Linux Mint 13 LTS, Linux Mint 17 LTS, Linux Mint 17.1 LTS, Linux Mint 17.2 LTS

Power

Media Handling

Media Sizes:	ANSI A (Letter) (216 x 279 mm), Legal (216 x 356 mm), Executive (184 x 267 mm), A4 (210 x 297 mm), A5 (148 x 210 mm), A3 (297 x 420 mm), A6 (105 x 148 mm), Folio (216 x 330 mm), Tabloid Extra (305 x 457 mm), JIS B4 (257 x 364 mm), SRA3 (320 x 450 mm), 101.6 x 152.4 mm, Statement (139.7 x 215.9 mm), Oficio (216 x 343 mm)
--------------	---

Envelope Sizes:	US No 10 (104.7 x 241.3 mm), International DL (110 x 220 mm), International C5 (162 x 229 mm), International B5 (176 x 250 mm), Monarch (98.4 x 190.5 mm), US No 9 (98.6 x 225.6 mm)
-----------------	--

Media Weight:	60 g/m ² - 256 g/m ²
---------------	--

Total Media Capacity:	1150 sheets
-----------------------	-------------

Media Feeders:	Bypass tray: 1 x automatic - 150 sheets weight: 60 g/m ² - 256 g/m ² ; Input tray: 2 x automatic - 500 sheets weight: 60 g/m ² - 256 g/m ²
----------------	--

Max Media Capacity:	6650 sheets
---------------------	-------------

Output Trays Capacity:	250 sheets
------------------------	------------

Duty Cycle

Monthly Duty Cycle (max):	250000 pages
---------------------------	--------------

Recommended Monthly Volume:	7000 - 50000 pages
-----------------------------	--------------------

Networking

Networking:	Print server
-------------	--------------

Remote Management Protocol:	SNMP 1, Telnet, SNMP 3, SNMP 2c, HTTP, HTTPS
-----------------------------	--

Security Protocols & Features:	LEAP, TLS, IPsec, 802.1x, TTLS, PEAP, MD5, MS-CHAPv2
--------------------------------	--

Expansion / Connectivity

Connections:	1 x USB 2.0 - 4 pin USB Type B ; 1 x Gigabit LAN - RJ-45 ; 3 x USB 2.0 host - 4 pin USB Type A
--------------	--

Power

Power Device:	Power supply - internal
Power Consumption Operational:	1050 Watt
Power Consumption Stand by:	200 Watt
Power Consumption Sleep:	2.2 Watt

Miscellaneous

Consumables Included:	1 x toner cartridge (black) - up to 18500 pages ISO/IEC 19798 ; 1 x toner cartridge (cyan) - up to 11500 pages ISO/IEC 19798 ; 1 x toner cartridge (magenta) - up to 11500 pages ISO/IEC 19798 ; 1 x toner cartridge (yellow) - up to 11500 pages ISO/IEC 19798 ; 1 x photoconductor unit (black) - up to 100000 pages at 5% coverage ; 1 x photoconductor unit (colour) - up to 90000 pages at 5% coverage
-----------------------	---

Compliant Standards:	FCC Class A certified, UL, C-Tick, cUL, GS, NOM, SABs, CB, CCC, DOC, ICES-003 Class A, SII, Green Mark, IEC 60825-1, FDA, UL-AR, BSMI Class A, CDRH, KC, CECP, CEL, EuP, Green Dot, VCCI Class A, Directive 1275/2008/EC, ECMA-370, EFTA, TER, CoC, ISO 9296, NOM-032, ISO 532B, TED, CCD 035 EcoLogo
----------------------	---

