

# Lexmark MarkNet N8352 - print server - USB



Not in stock

SKU	27X0135
Product Description:	Lexmark MarkNet N8352 - print server - USB
Device Type:	Print server
Form Factor:	External
Interface (Bus) Type:	USB
Dimensions (WxDxH):	15.2 cm x 22.9 cm x 4.1 cm
Weight:	170 g
Data Link Protocol:	802.11b/g/n, NFC

## General

Device Type:	Print server
Form Factor:	External
Interface (Bus) Type:	USB

## Networking

Connectivity Technology:	Wireless
Data Link Protocol:	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, NFC
Data Transfer Rate:	72 Mbps
Network / Transport Protocol:	TCP/IP, UDP/IP, NTP, ICMP/IP, IPSec, LPR/LPD, ARP, FTP, BOOTP, DHCP, DNS, RARP, SLP, DDNS
Remote Management Protocol:	SNMP 1, Telnet, SNMP 3, SNMP 2c, HTTP, HTTPS, TFTP, IPP 1.0, IPP 1.1, IPP 2.0
Frequency Band:	2.4 GHz
Compliant Standards:	IEEE 802.11b, IEEE 802.11g, IEEE 802.1x, IEEE 802.11i, IEEE 802.11n

## Miscellaneous

Cables Included:	1 x USB cable
Encryption Algorithm:	LEAP, MD5, 128-bit WEP, 64-bit WEP, TLS, PEAP, TTLS, WPA2, WPA2-Enterprise

## Compatibility Information

Designed For:	Lexmark C2425dw, C2535dw, CS310dn, CS310n, CS317dn, CS410dn, CS410dtn, CS410n, CS417dn, CS421dn, CS510de, CS510dte, CS517de, CS521dn, CS622de, CX310dn, CX310n, CX317dn, CX410de, CX410de DSV EG, CX410dte, CX410e, CX410e Gov S36, CX417de, CX421adn, CX510de, CX510de SPR Columbia, CX510de Statoil, CX510dhe, CX510dthe, CX517de, CX522ade, CX622ade, CX625ade, CX625adhe, MS310dn, MS312dn, MS315dn, MS317dn, MS410dn, MS415dn, MS417dn, MS510dn, MS510dtn, MS517dn, MS610de, MS610dn, MS610dte, MS617dn, MX310dn, MX317dn, MX410de, MX417de
---------------	--

## Environmental Parameters

Min Operating Temperature:	16 °C
Max Operating Temperature:	32 °C
Humidity Range Operating:	8 - 80%

## Dimensions & Weight

Width:	15.2 cm
Depth:	22.9 cm
Height:	4.1 cm
Weight:	170 g

## Software / System Requirements

Produktdatablad genereret d. 22-07-2024 09:25.

Vær opmærksom på at priser og lagerstatus var gældende på genereringstidspunktet og dermed ikke kan garanteres.

## Software / System Requirements

HP-UX 11.11, Novell NetWare 6.5, Novell NetWare 5.1 SP6 or later, Novell NetWare 6.0 SP3 or later, HP-UX 11.23, Microsoft Windows 7, IBM AIX 5.3, SunSoft Solaris x86 10, Red Hat Enterprise Linux WS 4, Microsoft Windows Vista, SuSE Linux Enterprise Server 11, Microsoft Windows Server 2008 R2, Apple MacOS X 10.6, SUSE Linux Enterprise Desktop 11, Microsoft Windows 7 64-bit Edition, Red Flag Linux 6.0, Debian GNU/Linux 5.0, SUSE Linux Enterprise Desktop 10, SuSE Linux Enterprise Server 10, Microsoft Windows Vista (64-bit versions), Red Hat Enterprise Linux WS 5, Microsoft Windows Server 2008, IBM AIX 6.1, Microsoft Windows Server 2008 x64 Edition, HP-UX 11.31, Linux Linpus Desktop 9.6, SunSoft Solaris SPARC Platform Edition 9, SunSoft Solaris SPARC Platform Edition 10, Apple MacOS X Lion 10.7, openSUSE 11.4, Windows 8, IBM AIX 7.1, Linux Mint 11, SunSoft Solaris x86 11, Debian GNU/Linux 6.0, Linux Mint 10, Red Hat Enterprise Linux WS 6, Ubuntu 12.04, Apple OS X 10.8 Mountain Lion, openSUSE 12.2, Windows 8 64-bit Edition, openSUSE 12.1, Linux Mint 12, SunSoft Solaris SPARC Platform Edition 11, Red Hat Fedora 17, Android 4.1.2 (Jelly Bean), Ubuntu 12.10, Android 4.2.2 (Jelly Bean), Android 4.3 (Jelly Bean), Windows 8.1 64-bit Edition, Microsoft Windows Server 2012 R2, Windows 8.1, Windows RT, Apple OS X 10.9 Mavericks, Red Hat Fedora 18, Linux Mint 13, PCLinuxOS 2011, Android 4.4.2 (KitKat), Microsoft Windows RT 8.1, Red Hat Fedora 19, Apple MacOS X 10.10, Apple iOS 4.2

**OS Required:**

