

Logitech Rally Bar - video conferencing device



In Stock(33)

SKU	960-001311
Product Description:	Logitech Rally Bar - video conferencing device
Device Type:	Video conferencing device
Dimensions (WxDxH):	91 cm x 16.4 cm x 13.05 cm
Weight:	7.08 kg
Video Input:	Digital video camera - SuperSpeed USB 3.0
Audio Input:	6-microphone array - beamforming
Audio Output:	Speaker(s)

General

Device Type:	Video conferencing device
Security:	128 bit AES
Width:	91 cm
Depth:	16.4 cm
Height:	13.05 cm
Weight:	7.08 kg
Enclosure Colour:	Graphite

Video Input

Type:	Digital video camera (colour) - desktop
Interface Type:	SuperSpeed USB 3.0
Digital Video Capture Resolution:	3840 x 2160
Video Modes:	480p, 720p, 1080p, 4K, 1440p, 900p
Optical Zoom:	5
Digital Zoom:	3
Camera Mechanical Design:	Pan / tilt / zoom

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	40 °C
Humidity Range Operating:	10 - 95%

Manufacturer Warranty

Service & Support:	Limited warranty - 2 years
--------------------	----------------------------

Software / System Requirements

OS Required:	Apple MacOS, Microsoft Windows 7 / 8 / 8.1 / 10 or later
--------------	--

Power

Power Device:	Power adapter - external
Voltage Required:	AC 120/230 V

Miscellaneous

Cables Included:	1 x USB 3.0 Type C to Type A cable - 2.2 m 1 x HDMI cable - 2 m
Included Accessories:	Remote control
Software Certification:	Zoom Certified, Certified for Microsoft Teams
Compliant Standards:	Plug and Play

Expansion / Connectivity

Video Input

Features:	RightLight technology, RightSound technology, Wide Dynamic Range (WDR), Artificial Intelligence, Acoustic Echo Cancellation (AEC), 30 fps, microphone noise suppression technology, 52.2° field of view (vertical), 82.1° field of view (horizontal), 90° diagonal field of view, RightSight technology, Voice Activity Detector (VAD), -25° / +25° pan, -15° / +15° tilt
-----------	---

Audio Input

Type:	6-microphone array - integrated
Microphone Operation Mode:	Beamforming
Frequency Response:	90 - 16000 Hz

Audio Output

Type:	Speaker(s)
Total Harmonic Distortion (THD):	<2%

Expansion / Connectivity

Interfaces:	1 x network - Ethernet 10Base-T/100Base-TX/1000Base-T - RJ-45 3 x display / video - HDMI 3 x SuperSpeed USB 3.0 - 9 pin USB Type A 1 x USB-C 3.0 - 24 pin USB-C
-------------	---

Networking

Connectivity Technology:	Wireless, wired
Data Link Protocol:	Bluetooth, IEEE 802.11b, IEEE 802.11a, IEEE 802.11g, IEEE 802.11n, IEEE 802.11ac

Input Device

Type:	Remote control
Connectivity Technology:	Wireless

