

Moxa EDS-2008-ELP Series EDS-2008-ELP - switch - 8 ports - unmanaged



In Stock(7)

SKU	EDS-2008-ELP
Product Description:	Moxa EDS-2008-ELP Series EDS-2008-ELP - switch - 8 ports - unmanaged
Device Type:	Switch - 8 ports - unmanaged
Subtype:	Fast Ethernet
Ports:	8 x 10/100
Capacity:	Packet buffer size: 4 Mbit
MAC Address Table Size:	8K entries
Features:	Flow control, auto-negotiation, auto-uplink (auto MDI/MDI-X), store and forward, half duplex mode, full duplex mode, Quality of Service (QoS), plastic housing, broadcast storm protection

General

Device Type:	Switch - 8 ports - unmanaged
Enclosure Type:	DIN rail mountable
Subtype:	Fast Ethernet
Ports:	8 x 10/100
Capacity:	Packet buffer size: 4 Mbit
MAC Address Table Size:	8K entries

Features: Flow control, auto-negotiation, auto-uplink (auto MDI/MDI-X), store and forward, half duplex mode, full duplex mode, Quality of Service (QoS), plastic housing, broadcast storm protection

Compliant Standards: IEEE 802.3, IEEE 802.3u, IEEE 802.1p, IEEE 802.3x

Expansion / Connectivity

Interfaces: 8 x 100Base-TX RJ-45

Environmental Parameters

Min Operating Temperature:	-10 °C
Max Operating Temperature:	60 °C
Humidity Range Operating:	5 - 95% (non-condensing)
Min Storage Temperature:	-40 °C
Max Storage Temperature:	85 °C

Manufacturer Warranty

Service & Support: Limited warranty - 5 years

Dimensions & Weight

Width:	3.6 cm
Depth:	6.5 cm
Height:	8.1 cm
Weight:	90 g

Miscellaneous

Miscellaneous

Rack Mounting Kit: Optional

MTBF: 3,472,660 hours

Compliant Standards: EN 61000-4-4, EN 61000-4-2, EN 61000-4-3, EN 61000-4-6, EN 61000-4-5, FCC, EN 61000-4-8, UL 60950-1, IEC 60068-2-27, IEC 60068-2-32, IEC 60068-2-6, UL 508, cULus, FCC Part 15 B Class A, IP40, EN 50121, NEMA TS-2, EN 55022 Class A, IEEE 1588

Power

Voltage Required: DC 12/24/48 V

Features: Power Polarity Reverse Protect, Overload Current Protection

