

Moxa NPort 5150A - device server



Not in stock

SKU	NP-P5150A
Product Description:	Moxa NPort 5150A - device server
Device Type:	Device server
Form Factor:	External
Data Link Protocol:	Ethernet, Fast Ethernet, RS-232, RS-422, RS-485
OS Required:	SCO OpenServer, UnixWare 7, SCO Unix, QNX, FreeBSD, UnixWare 2.1, HP-UX 11i, Microsoft Windows XP Embedded, Linux 2.4.x, Apple MacOS X 10.3, IBM AIX 5.x, Microsoft Windows 95/98/ME/NT/2000/XP, SunSoft Solaris 10, Linux 2.6.x, Microsoft Windows CE 5.0, Microsoft Windows 2003, Microsoft Windows Server 2008, Microsoft Windows CE 6.0, Microsoft Windows Vista / 7
Microsoft Certification:	Compatible with Windows 7
Dimensions (WxDxH):	5.2 cm x 8 cm x 2.2 cm



General

Device Type:	Device server
Width:	5.2 cm
Depth:	8 cm
Height:	2.2 cm
Weight:	340 g

Networking

Form Factor:	External
Connectivity Technology:	Wired
Data Transfer Rate:	921.6 Kbps
Data Link Protocol:	Ethernet, Fast Ethernet, RS-232, RS-422, RS-485
Network / Transport Protocol:	TCP/IP, UDP/IP, ICMP/IP, SMTP, BOOTP, DHCP, DNS
Routing Protocol:	IGMPv2, IGMP
Remote Management Protocol:	SNMP 1, Telnet, HTTP
Status Indicators:	Transmit, receive, link/activity

Features:

DHCP support, BOOTP support, auto-uplink (auto MDI/MDI-X), firmware upgradable, wall mountable, 15 KV Electrostatic Discharge Protection, DIN rail mountable

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	60 °C
Humidity Range Operating:	5 - 95% (non-condensing)

Manufacturer Warranty

Service & Support:	Limited warranty - 5 years
--------------------	----------------------------

Software / System Requirements

OS Required:	SCO OpenServer, UnixWare 7, SCO Unix, QNX, FreeBSD, UnixWare 2.1, HP-UX 11i, Microsoft Windows XP Embedded, Linux 2.4.x, Apple MacOS X 10.3, IBM AIX 5.x, Microsoft Windows 95/98/ME/NT/2000/XP, SunSoft Solaris 10, Linux 2.6.x, Microsoft Windows CE 5.0, Microsoft Windows 2003, Microsoft Windows Server 2008, Microsoft Windows CE 6.0, Microsoft Windows Vista / 7
--------------	--

Power

Power Device:	External power adapter
---------------	------------------------

Miscellaneous

MTBF:	2,231,530 hours
-------	-----------------

Compatible with Windows 7:	"Compatible with Windows 7" software and devices carry Microsoft's assurance that these products have passed tests for compatibility and reliability with 32-bit and 64-bit Windows 7.
----------------------------	--

Compliant Standards:	FCC Class B certified, FCC Class A certified, UL, EN55024, EN55022 Class A, EN 61000-4-4, FCC Part 15, EN 61000-4-5, IEC 60950-1, EN 60950-1
----------------------	--

Expansion / Connectivity

Interfaces:	1 x RS-232/422/485 - DB-9 1 x 100Base-TX - RJ-45
-------------	--