

Moxa NPort 5210A - device server



Not in stock

SKU	NP-5210A
Product Description:	Moxa NPort 5210A - device server
Device Type:	Device server
Form Factor:	External
Ports Qty:	2
Data Link Protocol:	Ethernet, Fast Ethernet, RS-232
OS Required:	SCO OpenServer, UnixWare 7, SCO Unix, QNX, FreeBSD, UnixWare 2.1, HP-UX 11i, Apple MacOS X 10.3, IBM AIX 5.x, Microsoft Windows 95/98/ME/NT/2000/XP, SunSoft Solaris 10, Linux Kernel 2.4 or later, Linux Kernel 2.6 or later, Microsoft Windows Server 2008 (32/64-bits), Microsoft Windows Server 2003 (32/64-bits), Microsoft Windows Vista / 7, Microsoft Windows Vista / XP / 7 (64-bit versions)
Power:	DC 12 - 48 V

General

Device Type:	Device server
Width:	7.7 cm
Depth:	2.6 cm
Height:	11.1 cm
Weight:	340 g

Networking

Form Factor:	External
Ports Qty:	2
Connectivity Technology:	Wired
Data Transfer Rate:	921.6 Kbps
Data Link Protocol:	Ethernet, Fast Ethernet, RS-232
Network / Transport Protocol:	TCP/IP, UDP/IP, ICMP/IP, SMTP, BOOTP, DHCP, DNS

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	60 °C
Humidity Range Operating:	5 - 95% (non-condensing)

Manufacturer Warranty

Service & Support:	Limited warranty - 5 years
--------------------	----------------------------

Software / System Requirements

Software Included:	Drivers & Utilities
--------------------	---------------------

Networking

Routing Protocol: IGMPv2, IGMP

Remote Management Protocol: SNMP 1, Telnet, HTTP

Features: Flow control, auto-uplink (auto MDI/MDI-X), surge protection, 15 KV Electrostatic Discharge Protection, reset button, Automatic Data Direction Control (ADDC), rugged

Software / System Requirements

OS Required: SCO OpenServer, UnixWare 7, SCO Unix, QNX, FreeBSD, UnixWare 2.1, HP-UX 11i, Apple MacOS X 10.3, IBM AIX 5.x, Microsoft Windows 95/98/ME/NT/2000/XP, SunSoft Solaris 10, Linux Kernel 2.4 or later, Linux Kernel 2.6 or later, Microsoft Windows Server 2008 (32/64-bits), Microsoft Windows Server 2003 (32/64-bits), Microsoft Windows Vista / 7, Microsoft Windows Vista / XP / 7 (64-bit versions)

Power

Voltage Required: DC 12 - 48 V

Miscellaneous

MTBF: 847,750 hours

Compliant Standards: IEC 61000-4-5, EN55024, EN55022 Class A, EN 61000-4-4, EN 61000-4-5, FCC, RoHS, UL 60950-1, EN 60950-1, cULus, FCC Part 15 B Class A

Expansion / Connectivity

Interfaces: 2 x RS-232 - DB-9 ; 1 x 100Base-TX - RJ-45

