

# Moxa NPort 6250 - terminal server



Not in stock

SKU	NP-6250
Product Description:	Moxa NPort 6250 - terminal server
Device Type:	Terminal server
Form Factor:	External
Localisation:	Europe
Ports Qty:	2
Data Link Protocol:	Ethernet, Fast Ethernet, RS-232, RS-422, RS-485
OS Required:	SCO Unix, QNX, FreeBSD, UnixWare 2.1, UnixWare 7.0, HP-UX 11i, Microsoft Windows XP Embedded, Linux 2.4.x, IBM AIX 5.x, Microsoft Windows 95/98/ME/NT/2000/XP, SunSoft Solaris 10, Linux 2.6.x, Microsoft Windows CE 5.0, Microsoft Windows 2003, Microsoft Windows Server 2008, Microsoft Windows Vista (32/64 bits), Microsoft Windows CE 6.0

## General

Device Type:	Terminal server
Width:	7.7 cm
Depth:	11.1 cm
Height:	2.8 cm
Weight:	0.73 kg
Localisation:	Europe

## Networking

Form Factor:	External
Ports Qty:	2
Connectivity Technology:	Wired
Data Transfer Rate:	921.6 Kbps
Data Link Protocol:	Ethernet, Fast Ethernet, RS-232, RS-422, RS-485
Network / Transport Protocol:	TCP/IP, UDP/IP, ICMP/IP, PPPoE, ARP, SMTP, BOOTP, DHCP, DNS
Routing Protocol:	RIP-1, RIP-2, static IP routing

## Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	55 °C
Humidity Range Operating:	5 - 95% (non-condensing)

## Manufacturer Warranty

Service & Support: Limited warranty - 5 years

## Software / System Requirements

Software Included:	Drivers & Utilities
OS Required:	SCO Unix, QNX, FreeBSD, UnixWare 2.1, UnixWare 7.0, HP-UX 11i, Microsoft Windows XP Embedded, Linux 2.4.x, IBM AIX 5.x, Microsoft Windows 95/98/ME/NT/2000/XP, SunSoft Solaris 10, Linux 2.6.x, Microsoft Windows CE 5.0, Microsoft Windows 2003, Microsoft Windows Server 2008, Microsoft Windows Vista (32/64 bits), Microsoft Windows CE 6.0

## Networking

**Remote Management Protocol:** SNMP 1, Telnet, SNMP 3, SNMP 2c, HTTP, HTTPS, SSH

**Status Indicators:** Power, link/activity

**Features:** Flow control, DHCP support, BOOTP support, auto-uplink (auto MDI/MDI-X), IPv6 support, wall mountable, 15 KV Electrostatic Discharge Protection, DIN rail mountable

**Encryption Algorithm:** DES, Triple DES, AES, SSL

**Authentication Method:** Secure Shell (SSH)

## Power

**Power Device:** External power adapter

## Miscellaneous

**MTBF:** 226,128 hours

**Compliant Standards:** EN55024, EN55022 Class A, EN 61000-4-4, EN 61000-4-2, EN 61000-4-3, EN 61000-4-6, EN 61000-4-5, FCC, EN 61000-4-11, RoHS, EN 61000-4-8, UL 60950-1, EN 60950-1, WEEE, IEC 60068-2-32, IEC 60068-2-6, FCC Part 15 B Class A

## Expansion / Connectivity

**Interfaces:** 2 x RS-232/422/485 - DB-9 ; 1 x 100Base-TX - RJ-45

## Communications

**Supported Flash Memory Cards:** SD Memory Card

