

Opticon OPR-3201 - barcode scanner



In Stock(22)

SKU	11789
Product Description:	Opticon OPR-3201 - barcode scanner
Type:	Barcode scanner - handheld - USB - decoded
Colour:	Black
Minimum Bar Width:	5 mil
Scan Field Width:	20 mm - 500 mm
Scan Element Type:	Visible laser diode
Scan Speed:	100 scan / sec

General

Type:	Barcode scanner - handheld
Colour:	Black

Environmental Parameters

Min Operating Temperature:	-5 °C
Max Operating Temperature:	50 °C
Humidity Range Operating:	5 - 95% (non-condensing)
Drop Specification:	1.5 m to concrete

Dimensions & Weight

Width:	5.6 cm
Depth:	10.9 cm
Height:	14.9 cm
Weight:	80 g

Miscellaneous

Included Accessories:	Stand
Cables Included:	1 x USB cable - external
Compliant Standards:	VCCI, FCC, RoHS, IEC 60825-1, JIS C 6802 Class 2

Expansion / Connectivity

Interfaces:	1 x USB - Type A
-------------	------------------

Barcode

Interface Type:	USB
-----------------	-----



Barcode

Minimum Bar Width:	5 mil
--------------------	-------

Scan Field Width:	20 mm - 500 mm
-------------------	----------------

Scan Element Type:	Visible laser diode
--------------------	---------------------

Light Source Wave Length:	650 nm
---------------------------	--------

Scan Mode:	Single-pass
------------	-------------

Scan Speed:	100 scan / sec
-------------	----------------

Skew (Degrees):	50
-----------------	----

Pitch (Degrees):	35
------------------	----

Print Contrast Signal (PCS):	35%
------------------------------	-----

Decode Capability:	EAN/JAN, Code 93, Matrix 2 of 5, Industrial 2 of 5, Code 39, NW-7, IATA, ISBN, GS1 DataBar, Telepen, MicroPDF417, Codabar, Code 128, Code 11, UPC, Interleaved 2 of 5, PDF417, MSI-Plessey, China Post, Korea Post, Trioptic Code, Plessey, EAN-UCC Composite, ISSN, S-Code
--------------------	---

TTL Decoding:	Decoded
---------------	---------

Connectivity Technology:	Wired
--------------------------	-------

OK Notification:	Beeper, LED indicator
------------------	-----------------------

Features:	Triggered
-----------	-----------