

Panasonic PT-MZ10KLBEJ - 3LCD projector - no lens - anthrazit



Not in stock

SKU	PT-MZ10KLBEJ
Product Description:	Panasonic PT-MZ10KLBEJ - 3LCD projector - no lens - anthrazit
Device Type:	3LCD projector
Colour:	Anthrazit
Brightness:	10000 lumens
Contrast Ratio:	3000000:1 (dynamic)
Resolution:	WUXGA (1920 x 1200)
Native Aspect Ratio:	16:10



General

Device Type:	3LCD projector
Networking:	Ethernet
Enclosure Colour:	Anthrazit

Projector

Brightness:	10000 lumens
Contrast Ratio:	3000000:1 (dynamic)
Image Size:	178 cm - 2540 cm
Resolution:	WUXGA - WUXGA (1920 x 1200)
Native Aspect Ratio:	16:10
Display Format:	6,912,000 pixels (1920 x 1200) x 3
Bulb type:	Laser diode
Bulb life cycle:	Up to 20000 hour(s) - normal mode ; Up to 24000 hour(s) - economic mode
Controls & Adjustments:	Keystone correction
Features:	Deep Color, PLink, 360° projection, art-net compatible

Lens

Type:	No lens
-------	---------

Video Input

Video Interfaces:	HDMI, DVI, SD-SDI, RGB, DIGITAL LINK
-------------------	--------------------------------------

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	45 °C
Humidity Range Operating:	10 - 80% (non-condensing)
Sound Emission:	35 dB

Dimensions & Weight

Width:	65 cm
Depth:	44 cm
Height:	18.5 cm
Weight:	22.3 kg

Power

Power Source:	AC
Voltage Required:	AC 120/230 V (50/60 Hz)
Power Consumption Operational:	650 Watt

Miscellaneous

Security Features:	Security lock slot (cable lock sold separately)
Security Slot Type:	Kensington security slot

Expansion / Connectivity

Interfaces:	1 x 3G/HD/SD-SDI input - BNC ; 1 x HDMI - 19 pin HDMI Type A ; 1 x DVI-D ; 1 x RGB input - 15 pin HD D-Sub (HD-15) ; 1 x serial RS-232C input - 9 pin D-Sub (DB-9) (management) ; 1 x serial RS-232C output - 9 pin D-Sub (DB-9) (male) (management) ; 1 x remote control input - mini-phone stereo 3.5 mm (management) ; 1 x remote control output - mini-phone stereo 3.5 mm (management) ; 1 x remote control output - 9 pin D-Sub (DB-9) (management) ; 1 x DIGITAL LINK - RJ-45 ; 1 x network - RJ-45 ; 1 x USB - 4 pin USB Type A
-------------	---