

Panasonic PT-MZ570LEJ - LCD projector - no lens - LAN



Not in stock

SKU	PT-MZ570LEJ
Product Description:	Panasonic PT-MZ570LEJ - LCD projector - no lens - LAN
Device Type:	LCD projector - 1080p
Built-in Devices:	Speaker
Brightness:	5500 lumens
Contrast Ratio:	3000000:1 (dynamic)
Resolution:	WUXGA (1920 x 1200)
Native Aspect Ratio:	16:10

General

Device Type:	LCD projector - 1080p
Built-in Devices:	Speaker
Networking:	Ethernet

Projector

Brightness:	5500 lumens
Contrast Ratio:	3000000:1 (dynamic)
Image Size:	103 cm - 1057 cm
Uniformity:	90 %
Resolution:	WUXGA - WUXGA (1920 x 1200)
Native Aspect Ratio:	16:10
Video Bandwidth:	162 MHz
Display Format:	6,912,000 pixels (1920 x 1200) x 3
Max Sync Rate (V x H):	100 Hz x 91 kHz
Bulb type:	Laser diode
Controls & Adjustments:	Keystone correction, lens shift dial (horizontal), lens shift dial (vertical)

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	45 °C
Humidity Range Operating:	20 - 80% (non-condensing)
Sound Emission:	33 dB
Sound Emission (Economic Mode):	28 dB

Dimensions & Weight

Width:	56 cm
Depth:	42.8 cm
Height:	20.5 cm
Weight:	15.2 kg

Power

Power Source:	AC
Voltage Required:	AC 120/230 V (50/60 Hz)

Miscellaneous

Included Accessories:	2 x AAA batteries, wireless / wired remote control, double packing case
Compliant Standards:	ISO 21118

Expansion / Connectivity

Projector

Features:

High-bandwidth Digital Content Protection System (HDCP), Daylight View Technology, 3LCD Technology, Deep Color, PJlink, DICOM Simulation Mode, Dust Resistant Cabinet, Detail Clarity Processor 4, 360° projection, Digital Link, SOLID SHINE Laser Technology, 24/7 operation

Lens

Type:	No lens
Keystone Correction Direction:	Horizontal, vertical
Vertical Keystone Correction:	-30 / +30
Horizontal Keystone Correction:	-25 / +25
Lens Shift Type:	Powered
Lens Shift Direction:	Horizontal, vertical

Expansion / Connectivity

Interfaces:	1 x HDMI input - 19 pin HDMI Type A ; 1 x composite / component video / RGB output - BNC x 5 ; 1 x component video / RGB input - 15 pin HD D-Sub (HD-15) ; 1 x serial RS-232C input - 9 pin D-Sub (DB-9) (management) ; 1 x serial RS-232 input - 9 pin D-Sub (DB-9) (management) ; 1 x remote control input - mini-phone 3.5 mm (management) ; 1 x USB (power only) - 4 pin USB Type A (power only) ; 1 x USB - 4 pin USB Type A ; 1 x network - RJ-45 (management) ; 1 x network - RJ-45 ; 1 x composite video input - RCA ; 1 x component video / RGB output - 15 pin HD D-Sub (HD-15) ; 1 x audio line-in - RCA x 2 ; 2 x audio line-in - mini-phone stereo 3.5 mm ; 1 x audio line-out - mini-phone stereo 3.5 mm
-------------	--

Speakers

Type:	Integrated
Sound Output Mode:	Mono
Output Power / Channel:	10 Watt
Speakers:	1 x mixed channel

Video Input

TV System:	NTSC, SECAM, PAL, PAL-N, PAL-M, NTSC 4.43, PAL 60
Analogue video Signal:	RGB, composite video, component video
Video Interfaces:	HDMI, component video, composite video, RGB
Video Modes:	480p, 480i, 525i, 525p, 625p, 625i, 576i, 576p, 1080/24p, 1080/60i, 720/60p, 1080/50i, 720/50p, 1080/50p, 1080/60p, 1080/30p, 1080/25p, 750/50p, 750/60p, 1125/60i, 1125/60p, 1125/50i, 1125/24p, 1125/25p, 1125/30p, 1125/50p, 1035/60i, 1080/24sF, 1125/24sF

LAN and Wireless Image Transferring Protocols:	Wired LAN
--	-----------

