

Panasonic PT-MZ880WEJ - LCD projector - standard lens - LAN



Not in stock

SKU	PT-MZ880WEJ
Product Description:	Panasonic PT-MZ880WEJ - LCD projector - standard lens - LAN
Device Type:	LCD projector - 1080p
Brightness:	8000 lumens
Contrast Ratio:	3000000:1 (dynamic)
Resolution:	WUXGA (1920 x 1200)
Native Aspect Ratio:	16:10
Lens:	Standard lens

General

Device Type:	LCD projector - 1080p
Networking:	Ethernet

Projector

Brightness:	8000 lumens
Brightness (Reduced):	5600 lumens
Contrast Ratio:	3000000:1 (dynamic)
Image Size:	102 cm - 1016 cm
Throw Ratio:	1.61 - 2.76:1
Uniformity:	85 %
Resolution:	WUXGA - WUXGA (1920 x 1200)
Native Aspect Ratio:	16:10

Display Format:	2,304,000 pixels (1920 x 1200) x 3
Bulb type:	Laser diode
Bulb life cycle:	Up to 20000 hour(s) - normal mode Up to 24000 hour(s) - economic mode
Controls & Adjustments:	Keystone correction, lens shift dial (horizontal), lens shift dial (vertical)

Features:	Edge blending, High-bandwidth Digital Content Protection System (HDCP), Deep Color, PLink, Geometric Adjustment, Detail Clarity Processor 4, Digital Link
-----------	---

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	45 °C
Humidity Range Operating:	20 - 80% (non-condensing)
Sound Emission:	34 dB
Sound Emission (Economic Mode):	27 dB

Dimensions & Weight (Shipping)

Shipping Width:	75.6 cm
Shipping Depth:	54.5 cm
Shipping Height:	34.8 cm
Shipping Weight:	24.9 kg

Dimensions & Weight

Width:	56.1 cm
Depth:	43.7 cm
Height:	22.4 cm
Weight:	18.6 kg

Software / System Requirements

Software Included:	Logo Transfer Software, Multi Projector Monitoring & Control Software, Early Warning Software, Smart Projector Control App, Geometry Manager Pro
--------------------	--

Lens

Type:	Standard lens
Focus Type:	Powered
Lens Aperture:	F/1.7-2.3
Zoom Type:	Powered
Keystone Correction Direction:	Horizontal, vertical
Vertical Keystone Correction:	-25 / +25
Horizontal Keystone Correction:	-30 / +30
Lens Shift Direction:	Horizontal, vertical
Vertical Lens Shift:	67% / 67%
Horizontal Lens Shift:	35% / 35%

Video Input

Video Interfaces:	HDMI, component video, RGB, DIGITAL LINK
LAN and Wireless Image Transferring Protocols:	Wired LAN

Power

Power Source:	AC
Voltage Required:	AC 120/230 V (50/60 Hz)
Power Consumption Operational:	490 Watt
Power Consumption Stand by:	0.5 Watt

Miscellaneous

Included Accessories:	2 x AAA batteries, remote control, double packing case
Security Features:	Security lock slot (cable lock sold separately)
Security Slot Type:	Kensington security slot
Compliant Standards:	CEC, ISO/IEC 21118:2020

Expansion / Connectivity

Interfaces:	1 x USB - 4 pin USB Type A ; 1 x network - RJ-45 ; 1 x DIGITAL LINK - RJ-45 ; 3 x HDMI input - 19 pin HDMI Type A ; 1 x remote control input - 9 pin D-Sub (DB-9) (management) ; 1 x component video / RGB input - 15 pin HD D-Sub (HD-15) ; 1 x serial RS-232 input - 9 pin D-Sub (DB-9) (management) ; 1 x component video / RGB output - 15 pin HD D-Sub (HD-15) ; Audio line-in - mini-phone stereo 3.5 mm ; 1 x audio line-out - mini-phone stereo 3.5 mm ; 1 x remote control input - mini-phone 3.5 mm (management)
-------------	--

