

Panasonic PT-VX610 - LCD projector



Not in stock

SKU	PT-VX610EJ
Product Description:	Panasonic PT-VX610 - LCD projector
Device Type:	LCD projector
Brightness (White):	5500 lumens
Brightness (Colour):	5500 lumens
Contrast Ratio:	16000:1
Resolution:	XGA (1024 x 768)
Native Aspect Ratio:	4:3

General

Device Type:	LCD projector
Networking:	Ethernet

Projector

Brightness (White):	5500 lumens
Brightness (Colour):	5500 lumens
Contrast Ratio:	16000:1
Image Size:	76 cm - 762 cm
Throw Ratio:	1.17 - 1.90:1
Uniformity:	85 %
Resolution:	XGA - XGA (1024 x 768)
Native Aspect Ratio:	4:3
Video Bandwidth:	162 MHz
Display Format:	786,432 pixels (1,024 x 768) x 3
Max Sync Rate (V x H):	100 Hz x 91 kHz
Bulb type:	UHM 280 Watt
Bulb life cycle:	Up to 5000 hour(s) - normal mode Up to 7000 hour(s) - economic mode
Controls & Adjustments:	Keystone correction
Features:	PJlink

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	40 °C
Humidity Range Operating:	20 - 80% (non-condensing)
Sound Emission:	37 dB
Sound Emission (Economic Mode):	29 dB

Dimensions & Weight

Width:	38.9 cm
Depth:	33.2 cm
Height:	12.5 cm
Weight:	4.8 kg

Software / System Requirements

Software Included:	Drivers & Utilities, Logo Transfer Software, Multi Projector Monitoring & Control Software
--------------------	--

Power

Power Source:	AC
Voltage Required:	AC 120/230 V (50/60 Hz)
Power Consumption Operational:	400 Watt
Power Consumption Stand by:	8 Watt

Lens

Focus Type:	Manual
Lens Aperture:	F/1.6-1.9
Zoom Type:	Manual
Zoom Factor:	1.6x
Keystone Correction Direction:	Horizontal, vertical
Vertical Keystone Correction:	-35 / +35
Horizontal Keystone Correction:	-35 / +35
Lens Shift Type:	Manual
Lens Shift Direction:	Vertical
Vertical Lens Shift:	40% / 40%

Miscellaneous

Included Accessories:	2 x AAA batteries, wireless remote control, cable holder
Cables Included:	1 x VGA cable
Security Features:	Security lock slot (cable lock sold separately)
Security Slot Type:	Kensington security slot

Expansion / Connectivity

Interfaces:	2 x HDMI input - 19 pin HDMI Type A ; 1 x component video / RGB input - 15 pin HD D-Sub (HD-15) ; 1 x composite video output - RCA ; 1 x VGA input / output - 15 pin HD D-Sub (HD-15) ; 2 x audio line-in - mini-phone stereo 3.5 mm ; 1 x audio line-in - RCA x 2 ; 1 x audio line-out - mini-phone stereo 3.5 mm ; 1 x USB - 4 pin USB Type A ; 1 x serial RS-232 input - 9 pin D-Sub (DB-9) (management) ; 1 x network - RJ-45
-------------	---

Speakers

Type:	Integrated
Sound Output Mode:	Mono
Output Power / Channel:	10 Watt
Speakers:	1 x mixed channel - 4 cm

Video Input

TV System:	NTSC, SECAM, PAL, PAL-N, PAL-M, NTSC 4.43, PAL 60
Analogue video Signal:	RGB, composite video, component video
Video Interfaces:	HDMI, component video, composite video, RGB
Video Modes:	480p, 480i, 525i, 525p, 625p, 625i, 576i, 576p, 1080/24p, 1080/60i, 720/60p, 1080/50i, 720/50p, 1080/50p, 1080/60p, 1080/30p, 1080/25p, 750/50p, 750/60p, 1125/60i, 1125/60p, 1125/50i, 1125/24p, 1125/25p, 1125/30p, 1125/50p, 1080/24sF, 1125/24sF

