

APC Smart-UPS SMT750IC - UPS - 500 Watt - 750 VA - with APC SmartConnect



06-08-2021

SKU	SMT750IC
Product Description:	APC Smart-UPS SMT750IC - UPS - 500 Watt - 750 VA - with APC SmartConnect
Device Type:	UPS - external
Weight:	13.18 kg
Input Voltage:	AC 220/230/240 V
Output Voltage:	AC 230 V ± 5%
Power Capacity:	500 Watt / 750 VA
Input Connectors:	1 x power IEC 60320 C14

General

Device Type:	UPS - external
Colour:	Black
Bundled with:	APC SmartConnect

Dimensions & Weight (Shipping)

Shipping Width:	27.8 cm
Shipping Depth:	39.9 cm
Shipping Height:	30.1 cm
Shipping Weight:	14.23 kg

Power Device

UPS Technology:	Line interactive
Input Voltage:	AC 220/230/240 V
Input Voltage Range:	AC 160 - 286 V
Input Voltage Range (Adjustable):	AC 151 - 302 V
Frequency Provided:	50/60 Hz ± 3Hz
Frequency Required:	50/60 Hz ± 3Hz
Input Connectors:	1 x power IEC 60320 C14
Power Output Connectors Details:	6 x power IEC 60320 C13 ; 2 x IEC jumper
Output Voltage:	AC 230 V ± 5% - 50/60 Hz
Power Capacity:	500 Watt / 750 VA
Output Waveform:	Sinewave
Surge Suppression:	Yes
Surge Energy Rating:	540 Joules
Circuit Protection:	Circuit breaker

Dimensions & Weight

Width:	13.8 cm
Depth:	35.81 cm
Height:	15.75 cm
Weight:	13.18 kg

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	40 °C
Humidity Range Operating:	0 - 95%
Sound Emission:	40 dBA

Manufacturer Warranty

Service & Support:	Limited warranty - replace or repair - 3 years ; Limited warranty - batteries - 2 years
--------------------	---

Battery

Quantity:	1
Technology:	Lead Acid
Run Time (Up To):	4.6 min at full load 15.9 min at half load 103 min at 50 Watts 50.5 min at 100 Watts 21.7 min at 200 Watts 12 min at 300 Watts 7.3 min at 400 Watts
Recharge Time:	3 hours
Transfer Time:	6 ms
Features:	Maintenance free, sealed, leak-proof

Networking

Remote Management Interface:	RS-232, USB
------------------------------	-------------

Expansion / Connectivity

Interfaces:	1 x management (RS-232) - RJ-45 1 x management (USB)
Expansion Slots:	1 (total) / 1 (free) x SmartSlot

Software / System Requirements

Software Included:	APC PowerChute Business Edition
--------------------	---------------------------------

Miscellaneous

Cables Included:	Serial cable - external USB cable - external Power cable 1.83 m
Features:	Audible alarm, LCD display, Automatic Voltage Regulation (AVR), cold-start function, automatic self-test, predictive failure notification, hot-swappable batteries, energy metre
Compliant Standards:	CSA, UL 1778, VDE, IEC 62040-2, RoHS, REACH, EN 62040-2, EAC, RCM, IEC 62040-1, EN 62040-1

