

Sony SRG-120DS - conference camera



16-05-2024

SKU	SRG-120DS
Product Description:	Sony SRG-120DS - conference camera
Device Type:	Conference camera - pan / tilt / zoom
Dimensions (WxDxH):	15.3 cm x 15.3 cm x 15.6 cm
Weight:	1.6 kg
Connectivity Technology:	Wired
Camera:	Colour - 1000 TVL
Optical Zoom:	12 x

General

Device Type:	Conference camera
Connectivity Technology:	Wired
Width:	15.3 cm
Depth:	15.3 cm
Height:	15.6 cm
Weight:	1.6 kg

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	40 °C

Power

Power Requirements:	DC 12 V
Power Device:	16.8 Watt

Camera

Type:	Colour - pan / tilt / zoom
Horizontal Resolution (TV Lines):	1000
Max Digital Video Resolution:	1920 x 1080
Video Modes:	1080/50i, 720/50p, 1080/50p, 1080/25p, 720/25p, 1080/59.94i, 720/59.94p, 1080/59.54p, 1080/29.87p
Digital Zoom:	12
Exposure Range:	1/1 sec - 1/10000 sec
Minimum Illumination:	1.8 lux F1.8 - 50 IRE
Digital Video Capture Resolution:	1920 x 1080
Frame Rate (max):	60 frames per second

Expansion / Connectivity

Ports:	LAN - RJ-45 SDI - BNC VISCA input VISCA output
--------	--

Interfaces

Video:	3G-SDI
Control Interface:	RS-232

Tilting

Range (degree):	-25 to +25
Speed (degree/sec):	Up to 126

Panning

Range (degree):	-100 to +100
Speed (degree/sec):	Up to 300

Lens Construction

Type:	Motorized zoom
-------	----------------

Camera

Features:	Manual white balance, white balance, auto exposure control, Wide Dynamic Range (WDR), Automatic Tracing White (ATW), manual gain control, auto gain control, auto white balance
-----------	---

Lens Construction

Optical Zoom:	12 x
Focal Length:	3.9 mm - 46.8 mm
Lens Iris:	F/1.8-2.0
Focus Adjustment:	Automatic, manual
Horizontal Field of View (degree):	71

Image Sensor

Type:	2.1 MP Exmor CMOS 1/2.8"
-------	--------------------------

