

Sony VPL-FHZ131 - 3LCD projector - no lens - LAN - black



16-10-2024

SKU	VPL-FHZ131/B
Product Description:	Sony VPL-FHZ131 - 3LCD projector - no lens - LAN - black
Device Type:	3LCD projector
Colour:	Black
Brightness:	13600 lumens
Brightness (Colour):	13000 lumens
Resolution:	WUXGA (1920 x 1200)
Native Aspect Ratio:	16:10

General

Device Type:	3LCD projector
Networking:	Gigabit Ethernet
Enclosure Colour:	Black

Projector

Brightness:	13600 lumens
Brightness (Colour):	13000 lumens
Brightness (Reduced):	8600 lumens
Image Size:	152 cm - 1524 cm
Digital Zoom Factor:	4x
Resolution:	WUXGA - WUXGA (1920 x 1200)
Native Aspect Ratio:	16:10
Display Format:	6,910,000 pixels (1920 x 1200) x 3
Max Sync Rate (V x H):	92 Hz x 92 kHz
Bulb type:	Laser diode
Bulb life cycle:	Up to 20000 hour(s)
Controls & Adjustments:	Keystone correction, lens shift dial (horizontal), lens shift dial (vertical)

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	45 °C
Humidity Range Operating:	20 - 80% (non-condensing)

Dimensions & Weight

Width:	54.4 cm
Depth:	56.4 cm
Height:	20.5 cm
Weight:	31 kg

Power

Power Source:	AC
Voltage Required:	AC 120 V (50/60 Hz)
Power Consumption Operational:	1076 Watt
Power Consumption Stand by:	0.5 Watt

Miscellaneous

Included Accessories:	2 x AA batteries, remote control, plug holder
Security Features:	Security lock slot (cable lock sold separately)

Projector

OSD Languages: Multilingual

Features: Picture by picture, 360° projection, Power Save Mode, Contrast Enhancer

Lens

Type: No lens

Zoom Type: Powered

Zoom Factor: 1.5x

Keystone Correction Direction: Horizontal, vertical, corner

Lens Shift Direction: Horizontal, vertical

Vertical Lens Shift: 51% / 51%

Horizontal Lens Shift: 99% / 99%

Miscellaneous

Security Slot Type: Kensington security slot

Compliant Standards: JIS C 6802 Class 1

Expansion / Connectivity

1 x component video / RGB input - BNC x 5 ; 1 x RGB input - 15 pin HD D-Sub (HD-15) ; 1 x DVI-D input - DVI-D ; 1 x HDMI input - 19 pin

Interfaces: HDMI Type A ; 1 x HDBaseT - RJ-45 ; 1 x VGA output - 15 pin HD D-Sub (HD-15) ; USB (management) ; Network - RJ-45 ; 1 x serial RS-232C - 9 pin D-Sub (DB-9)

Video Input

Video Interfaces: VGA, HDMI, component video, DVI, RGB

Video Modes: 1080/24p, 1080/60i, 480/60p, 720/60p, 1080/50i, 720/50p, 576/50p, 1080/50p, 1080/60p, 480/60i, 576/50i

LAN and Wireless Image Transferring Protocols: Wired LAN

