

Sony VPL-FHZ80 - 3LCD projector - standard lens - LAN - white



In Stock(4)

SKU	VPL-FHZ80
Product Description:	Sony VPL-FHZ80 - 3LCD projector - standard lens - LAN - white
Device Type:	3LCD projector - 1080p
Colour:	White
Brightness:	6500 lumens
Brightness (Colour):	6000 lumens
Contrast Ratio:	∞:1
Resolution:	WUXGA (1920 x 1200)

General

Device Type:	3LCD projector - 1080p
Networking:	Ethernet
Enclosure Colour:	White

Projector

Brightness:	6500 lumens
Brightness (Colour):	6000 lumens
Brightness (Reduced):	4800 lumens
Contrast Ratio:	∞:1
Image Size:	102 cm - 1524 cm
Throw Ratio:	1.39 - 2.23:1
Resolution:	WUXGA - WUXGA (1920 x 1200)
Native Aspect Ratio:	16:10
Display Format:	6,912,000 pixels (1920 x 1200) x 3
Max Sync Rate (V x H):	93 Hz x 63 kHz
Bulb type:	Laser diode
Bulb life cycle:	Up to 20000 hour(s) - standard mode Up to 30000 hour(s) - middle mode
Controls & Adjustments:	Keystone correction, lens shift dial (horizontal), lens shift dial (vertical)

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	45 °C
Humidity Range Operating:	20 - 80% (non-condensing)
Sound Emission:	36 dB
Sound Emission (Economic Mode):	34 dB

Dimensions & Weight

Width:	46 cm
Depth:	49.4 cm
Height:	16.9 cm
Weight:	13 kg

Power

Power Source:	AC
Voltage Required:	AC 100-240 V (50/60 Hz)
Power Consumption Operational:	397 Watt
Power Consumption Stand by:	0.5 Watt

Miscellaneous

Security Features:	Security lock slot (cable lock sold separately)
--------------------	---

Projector

Features:	Auto Input Search, High-bandwidth Digital Content Protection System (HDCP), 3LCD Technology, BrightEra, Cloning Function, Reality Creation, auto power on, Z-Phosphor light source, Bright View
-----------	---

Lens

Type:	Standard lens
Focus Type:	Powered
Zoom Type:	Powered
Zoom Factor:	1.6x
Keystone Correction Direction:	Horizontal, vertical
Vertical Keystone Correction:	-30 / +30
Horizontal Keystone Correction:	-30 / +30
Lens Shift Type:	Powered
Lens Shift Direction:	Horizontal, vertical
Vertical Lens Shift:	5% / 70%
Horizontal Lens Shift:	32% / 32%

Miscellaneous

Security Slot Type:	Kensington security slot
---------------------	--------------------------

Expansion / Connectivity

Interfaces:	1 x RGB input - 15 pin HD D-Sub (HD-15) ; 1 x audio line-in - mini-phone stereo 3.5 mm ; 1 x DVI-D input - 24+1 pin digital DVI ; 1 x HDMI input - 19 pin HDMI Type A ; 1 x HDBaseT - RJ-45 ; 1 x composite video input - BNC ; 1 x VGA output - 15 pin D-Sub (DB-15) ; 1 x audio line-out - mini-phone stereo 3.5 mm ; 1 x DVI-D output - 24+1 pin digital DVI ; 1 x remote control - 9 pin D-Sub (DB-9) ; 1 x network - RJ-45 ; 1 x remote control - mini-phone stereo 3.5 mm ; USB
-------------	---

Video Input

TV System:	NTSC, SECAM, PAL
Video Interfaces:	HDMI, DVI, RGB, HDBaseT
Video Modes:	1080/60i, 480/60p, 720/60p, 1080/50i, 720/50p, 576/50p, 1080/50p, 1080/60p, 480/60i, 576/50i, 3840/25p, 3840/24p, 3840/30p, 3840/60p, 4096/24p, 4096/60p, 4096/30p, 4096/25p
LAN and Wireless Image Transferring Protocols:	Wired LAN
DVI-D with HDCP Input:	Yes

